

# Material Safety Data Sheet

24 Hour Assistance:  
1-855-627-6350  
Rust-Oleum Industrial Flooring  
www.toughandeasyfloors.com

## Section 1 - Chemical Product / Company Information

Product Name: WDCARE QT 6PK WATCO LACQR  
FIN GLOSS Revision Date: 10/17/2011

Identification Number: 63041

Product Use/Class: Watco Brushing Lacquer

Supplier: Rust-Oleum Industrial Flooring  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA

Manufacturer: Rust-Oleum Industrial Flooring  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA

Preparer: Regulatory Department

## Section 2 - Composition / Information On Ingredients

| Chemical Name                   | CAS Number  | Weight % Less |               |                |              |                  |
|---------------------------------|-------------|---------------|---------------|----------------|--------------|------------------|
|                                 |             | Than          | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL CEILING |
| n-Butyl Acetate                 | 123-86-4    | 20.0          | 150 ppm       | 200 ppm        | 150 ppm      | N.E.             |
| Isopropyl Alcohol               | 67-63-0     | 15.0          | 200 ppm       | 400 ppm        | 400 ppm      | N.E.             |
| Xylene                          | 1330-20-7   | 15.0          | 100 ppm       | 150 ppm        | 100 ppm      | N.E.             |
| Ethylene Glycol Monobutyl Ether | 111-76-2    | 10.0          | 20 ppm        | N.E.           | 50 ppm       | N.E.             |
| n-Butanol                       | 71-36-3     | 10.0          | 20 ppm        | N.E.           | 100 ppm      | N.E.             |
| Methyl Isobutyl Ketone          | 108-10-1    | 10.0          | 50 ppm        | 75 ppm         | 100 ppm      | N.E.             |
| Nitrocellulose Resin Solution   | MIXTURE     | 10.0          | N.E.          | N.E.           | N.E.         | N.E.             |
| Aromatic Petroleum Distillates  | 64742-95-6  | 5.0           | N.E.          | N.E.           | N.E.         | N.E.             |
| Ethylbenzene                    | 100-41-4    | 5.0           | 100 ppm       | 125 ppm        | 100 ppm      | N.E.             |
| Nitrocellulose Resin Solution   | PROPRIETARY | 5.0           | N.E.          | N.E.           | N.E.         | N.E.             |
| 1,2,4-Trimethylbenzene          | 95-63-6     | 5.0           | 25 ppm        | N.E.           | N.E.         | N.E.             |

## Section 3 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: High vapor concentrations can irritate eyes, nose and respiratory passages. Causes nose and throat irritation. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Harmful if swallowed. Causes eye irritation. Flammable liquid and vapor.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: May be harmful if absorbed through skin. Prolonged or repeated skin contact may cause irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. May cause headaches and dizziness. Avoid breathing vapors or mists. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

## **Section 4 - First Aid Measures**

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

First Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

First Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

## **Section 5 - Fire Fighting Measures**

Flash Point: 53 F (Setaflash)

Extinguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire And Explosion Hazards: Isolate from heat, electrical equipment, sparks and open flame. Vapors can travel to a source of ignition and flash back. Vapors may form explosive mixtures with air.

Special Firefighting Procedures: Evacuate area and fight fire from a safe distance. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion.

## **Section 6 - Accidental Release Measures**

Steps To Be Taken If Material Is Released Or Spilled: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Eliminate all ignition sources; use explosion-proof equipment. Place material in a container and dispose of according to local, provincial, state and federal regulations.

## **Section 7 - Handling And Storage**

Handling: Wash thoroughly after handling. Wash hands before eating. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Use with adequate ventilation.

Storage: Keep container closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition.

## **Section 8 - Exposure Controls / Personal Protection**

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and

windows to achieve cross-ventilation.

**Respiratory Protection:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

**Skin Protection:** Nitrile or Neoprene gloves may afford adequate skin protection. Use impervious gloves to prevent skin contact and absorption of this material through the skin.

**Eye Protection:** Use safety eyewear designed to protect against splash of liquids.

**Other protective equipment:** Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

**Hygienic Practices:** Wash thoroughly with soap and water before eating, drinking or smoking.

## Section 9 - Physical And Chemical Properties

|                                 |                  |                   |                   |
|---------------------------------|------------------|-------------------|-------------------|
| Vapor Density:                  | Heavier than Air | Odor:             | Solvent Like      |
| Appearance:                     | Liquid           | Evaporation Rate: | Slower than Ether |
| Solubility in H <sub>2</sub> O: | Slight           | Freeze Point:     | N.D.              |
| Specific Gravity:               | 0.929            | pH:               | N.D.              |
| Physical State:                 | Liquid           |                   |                   |

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

**Conditions To Avoid:** Avoid all possible sources of ignition.

**Incompatibility:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**Hazardous Decomposition:** When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

| <b>Chemical Name</b>            | <b>LD50</b>            | <b>LC50</b>                      |
|---------------------------------|------------------------|----------------------------------|
| n-Butyl Acetate                 | 13100 mg/kg (Rat)      | 2000 ppm (Rat, Inhalation, 4 Hr) |
| Isopropyl Alcohol               | 4396 mg/kg (Rat, Oral) | 72.6 mg/L (Rat, Inhalation, 4Hr) |
| Xylene                          | 4300 mg/kg (Rat, Oral) | 5000 ppm (Rat, Inhalation, 4Hr)  |
| Ethylene Glycol Monobutyl Ether | 1519 mg/kg (Mouse)     | 700 ppm (Rat, 7Hr)               |
| n-Butanol                       | 2500 mg/kg (Rat)       | >8000 ppm (Rat, 4Hr)             |

|                                |                   |                     |
|--------------------------------|-------------------|---------------------|
| Methyl Isobutyl Ketone         | 2080 mg/m3 (Rat)  | 23300 mg/m3 (Mouse) |
| Nitrocellulose Resin Solution  | >5000 mg/kg (Rat) | N.E.                |
| Aromatic Petroleum Distillates | 4900 mg/kg (Rat)  | N.E.                |
| Ethylbenzene                   | 3500 mg/kg (Rat)  | N.E.                |
| Nitrocellulose Resin Solution  | >5000 mg/kg (Rat) | N.E.                |
| 1,2,4-Trimethylbenzene         | N.E.              | N.E.                |

## Section 12 - Ecological Information

Ecological Information: Product is a mixture of listed components.

## Section 13 - Disposal Information

Disposal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

## Section 14 - Transportation Information

|                       | <b>Domestic (USDOT)</b> | <b>International (IMDG)</b> | <b>Air (IATA)</b> |
|-----------------------|-------------------------|-----------------------------|-------------------|
| Proper Shipping Name: | Consumer Commodity      | Paint                       | Paint             |
| Hazard Class:         | ORM-D                   | 3                           | 3                 |
| UN Number:            | N.A.                    | UN1263                      | UN1263            |
| Packing Group:        | N.A.                    | II                          | II                |
| Limited Quantity:     | No                      | IMDG 34-08, 3.4.7           | No                |

## Section 15 - Regulatory Information

### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

### SARA Section 313:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <b>Chemical Name</b>            | <b>CAS Number</b> |
|---------------------------------|-------------------|
| Isopropyl Alcohol               | 67-63-0           |
| Xylene                          | 1330-20-7         |
| Ethylene Glycol Monobutyl Ether | 111-76-2          |
| n-Butanol                       | 71-36-3           |
| Methyl Isobutyl Ketone          | 108-10-1          |
| Ethylbenzene                    | 100-41-4          |

### Toxic Substances Control Act:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of

TSCA 12(B) if exported from the United States:

### U.S. State Regulations: As follows -

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|----------------------|-------------------|
| Coconut Alkyd        | PROPRIETARY       |

#### Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u> | <u>CAS Number</u> |
|----------------------|-------------------|
| Coconut Alkyd        | PROPRIETARY       |
| Diisononyl Phthalate | 68515-48-0        |
| Resin                | PROPRIETARY       |

### International Regulations: As follows -

#### CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** B2 D2A D2B

|                                       |
|---------------------------------------|
| <b>Section 16 - Other Information</b> |
|---------------------------------------|

#### HMIS Ratings:

Health: 2\*

Flammability: 4

Physical Hazard: 0

Personal Protection: X

#### NFPA Ratings:

Health: 2

Flammability: 4

Instability: 0

**VOLATILE ORGANIC COMPOUNDS, g/L:** 675

**REASON FOR REVISION:** Regulatory Update

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Industrial Flooring believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Industrial Flooring makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply

with all applicable international, federal, state, and local laws and regulations.