

Effective Date: 9/24/98

PRODUCT IDENTITY: HERCULINER PROTECTIVE COATING

1. SUPPLIER OLD WORLD INDUSTRIES, INC. 4065 COMMERCIAL AVENUE NORTHBROOK, ILLINOIS 60062

PHONE: 847/559-2000

2. INGREDIENTS

HAZARDOUS COMPONENTS	CAS NO.	OSHA PEL	ACGIH TLV	STEL	% MAX
Xylene	1330-20-7	100 ppm	100 ppm	200 ppm	32

NOTE: See Section 11 – Possible Reporting Criteria

3. HAZARDS IDENTIFICATION

Hazard Rating System

Health: 0 Flammability: 3 Reactivity: 0

KEY: 1 = Slight 2 = Moderate 3 = High 4 = Extreme

HEALTH HAZARD DATA

Route(s) of Entry:

Inhalation? Moderate Skin? Low Ingestion? Low Eyes? Moderate

Health Hazards (Acute and Chronic):

Ingestion: Will cause severe distress in mouth and throat

Inhalation: Vapors can cause respiratory irritation Skin Contact: May cause blistering on contact Eye Contact: Can cause blistering and severe pain

Carcinogenicity:

NTP? No IARC Monographs? No OSHA Regulated? No ACGIH 1987-88 No

Medical Conditions

Aggravated by Exposure: None known

4. FIRST AID MEASURES

INGESTION: Get medical attention immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

INHALATION: Remove from contaminated area. Contact physician immediately.

SKIN CONTACT: Wipe with dry cloth or paper. Clean with solvent.

EYE CONTACT: Flush with large amounts of water as quickly as possible. Get medical attention quickly.

Continue flushing until help arrives.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 81 F (TCC)

Flammable Limits: 1.0

UEL: 7.0

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES: Vapors can form explosive mixtures with air. Vapors are heavier than air and will flow along surface to distant ignition sources and flash back.

UNUSUAL FIRE FIGHTING HAZARD: Keep away from heat, sources of ignition, oxidizers.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Small Spills: Absorb on suitable material (vermiculite, saw dust, sand). Sweep up.

Large Spills: Contain spill; absorb on vermiculite or sand; shovel up and send to registered landfill.

Waste Disposal Method: Contact local authorities for disposal rules.

7. HANDLING AND STORAGE

KEEP CONTAINER CLOSED WHEN NOT IN USE. CLEAN UP ALL SPILLS PROMPTLY. KEEP OUT OF THE REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Organic vapor filter suggested.

Ventilation: Maintain air movement.

Protective Gloves: Solvent and chemical resistant required.

Eye Protection: Plastic eye protection REQUIRED.

Other Protective

Clothing or Equipment: Boots suggested.

Work / Hygienic Practices: WASH HANDS AFTER HANDLING.

Application: Follow instructions; do not overuse product. Follow label directions.

9. PHYSICAL PROPERTIES

Boiling Point, Initial: 138° F

Vapor Pressure (mm Hg): 8 to 9 @ 25° C

Vapor Density (Air = 1): 3.0

pH: N/A

Solubility in Water: Forms solid gel

Appearance and Odor: Pigmented liquid, hydrocarbon

Specific Gravity (Water =1): C 865

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): N/A

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility (Materials to Avoid): Strong oxidizing agents, water

Hazardous Decomposition Products: Carbon monoxide

Hazardous Polymerization: WILL NOT OCCUR

11. REGULATORY INFORMATION

SARA Title III Reporting Requirements:

Section 302 No

Section 311 Yes

Section 312 Yes

Section 313 NOT REQUIRED

CERCLA / RCRA Reporting Requirements:

CERCLA: REQUIRED RCRA: REQUIRED

WHMIS: Yes

Biodegradability: NOT Biodegradable

DOT: (Highway & UPS Ground) DOT Consumer Commodity Exemption (Part 172, 150)

Label's Required: *Outer Packaging*: "Consumer Commodity - ORM-D" and ISO orientation arrows. *Pallets*: If "Consumer Commodity" on outer packaging is visible labeling not required. Otherwise label as "Consumer Commodity".

Container/Trailer: None required.

IATA (Air): IATA Limited Quantity Exemption (Part 2.8)

For Shipping of product 10 Liters and Under in one Package:

Packing Instruction Y309 (No UN Packaging Required).

Label's Required: Paint, Flammable Liquid, 3, ISO orientation arrows, shipper and consignee information, and the statement "LTD. QTY".

For Shipping of product over 10 Liters in one Package:

Packing Instruction 309 or 310 dependent aircraft type (UN Packaging Required).

Label's Required: Paint, Flammable Liquid, 3, ISO orientation arrows (cargo only aircraft label if applicable), shipper and consignee information.

11. REGULATORY INFORMATION - CONTINUED

IMDG (Ocean): IMDG Exemption for Limited Quantities (IMDG 18.3, 3.2.6)

Label's Required: *Outer Packaging*: (No requirements)

Pallets: Dangerous Goods in Limited Quantities (Class 3 Flammable)

Container: "Limited Quantities"

References:

Regulatory Standards: DOT Title 49, Code of Federal Regulations. Superfund Amendment Reauthorization Act of 1986, Title III. International Maritime Dangerous Goods (IMDG) Codes, Amdt. 28-96.

International Air Transportation Association (IATA) (Per International Civil Aviation Organization Technical Instructions) 39th Edition.

Toxic Substance Control

Act List (TSCA): Ingredients listed

Permissible Exposure

References: Registry of Toxic Effects of Chemical Substances

National Toxicology Programs (NTP) Report on Carcinogens

International Agency for Research on Cancer (IARC)

Monographs

Occupational Safety & Health Regulations

This information contained herein is based on data available too us and is believed to be correct. However, we make no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury from the use of the product described herein.

> For More Information or to Order Call Toll Free 1-877-HERCULINER or 1-877-437-2854

Home | Product Information | Q&A | Instructions | MSDS | Order Info | Hot Links | Contact Us

Copyright (C) 2001 Old World Industries, Inc. - All Rights Reserved.