

# **GDL Garage Door Lube**

MSDS Number: GDL Aerosol Revision Date: 02/24/06

Page 1 of 5

### PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** GDL Garage Door Lube

Revision Date: 02/24/06
MSDS Number: GDL Aerosol

**Product Code:** 8-GDL-S, 16-GDL, & GDL-TS

Manufacturer: The Blaster Chemical Companies, Inc.

8500 Sweet Valley Drive Valley View, Ohio 44125

(216) 901-5800 (216) 901-5801 fax

www.blasterproducts.com

# COMPOSITION/INFORMATION ON INGREDIENTS

### Ingredients:

2

Cas #	Chemical Name	Perc.
124389	Carbon dioxide (propellant)	<2%
64742478	Distillates, petroleum, hydrotreated lig	50-60%
64741657	Naphtha, petroleum, heavy alkylate	30-40%
68649423	Zinc Alkyl Dithiophosphate	<5%
63148629	Siloxanes and Silicones, di-Me	<12%

# 3 HAZARDS IDENTIFICATION

**Route of Entry:** Eyes, skin, inhalation, ingestion

**Target Organs:** 

**Inhalation:** Inhalation of spray mist may cause irritation to the respiratory tract.

**Skin Contact:** Repeated or prolonged contact with skin may cause mild irritation and possibly dermatitis.

**Eye Contact:** Likely to cause immediate or delayed irritation. Irritationwill show as redness and/or swelling of the

eyes.

**Ingestion:** Ingestion may cause irritation to the mouth, esophagus and stomach.

May aggravate a pre-existing skin and respiratory disorders.

**Physical Hazard:** Aerosol containers are pressurized (even when empty!) Do not expose to temperatures above 120° F. Do not puncture or burn can. Failure to observe these precautions may result in rapid and violent decompression of the container producing projectiles and atomization of the liquid contents.

**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.



# **GDL Garage Door Lube**

MSDS Number: GDL Aerosol Revision Date: 02/24/06

Page 2 of 5

# 4 FIRST AID MEASURES

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continuie

to monitor. Get medical attention.

Skin Contact: Remove contaminated clothing immediately! Wash skin with soap and water. If irritation develops, seek

medical attention.

Eye Contact: Flush eye(s) with water for 15 minutes. Get medical attention. If eye irritation presists, obtain medical

treatment.

**Ingestion:** Do not induce vomiting.! Get medical attention immediately!

# 5 FIRE FIGHTING MEASURES

Flashpoint: 145° F (TCC)

Unusual Fire & Explosion Hazard: Level 3 Aerosols - Contents Under Pressure

**Extinguishing Media:** Dry chemical. Carbon dioxide, halon or foam.

# 6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedure: Leaking cans should be put into suitable container until the internal pressure has dissipated.

**Waster Disposal Method:** Empty aerosol cans should be punctured and drained. Can and contents can then be incinerated. Dispose of in accordance with local, state and federal regulations.

# 7 HANDLING AND STORAGE

Handling Precautions: Use in accordance with good industrial workplace practices. Avoid unnecessary contact. Wash

thoroughly after handling. Use with good ventilation.

**Storage Requirements:** Store in a dry place away from excessive heat. Store containers with lids on and properly

labeled.

Do not store at temperatures above 120 degrees F.



# **GDL Garage Door Lube**

MSDS Number: GDL Aerosol Revision Date: 02/24/06

Page 3 of 5

### 8

### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering Controls: Protective Equipment:**  Eye wash stations and emegrency showers should be immediately available.

Eyes and Face: Standard safety glasses with splash shields typically offer adequate

protection. Where excessive splashing or spraying is possible, a face shield should be used.

Skin and clothing: Excessive contact should be avoided. Neoprene gloves, boots and aprons will provide adequate protection when contact cannot be avoided. Remove and wash any contaminated clothing immediately. Wash thoroughly after handling.

Respiratory: Good general ventilation should be sufficient to control airborne levels. Maintain airborne concentrations below OSHA established exposure limits of ingredients in Section 2.

**Exposure Guidelines/Other:** The Blaster Chemical Companies takes no responsibility for determining what measures are

required for personal protection in any specific application. This information should be used

with discretion.

# 9

### PHYSICAL AND CHEMICAL PROPERTIES

Appearance: clear **Physical State:** Liquid

Odor: citrus

pH: Not determined

Vapor Pressure: Not determined

Vapor Density: >1 (air = 1) **Boiling Point:** 180 F

Freezing/Melting Pt.: Not determined

Solubility:

Spec Grav./Density: 0.822 (water = 1)

**Heat Value:** Not determined VOC: Not determined Evap. Rate: >1 (NBA = 1) **Bulk Density:** Not determined Octanol: Not applicable Molecular Weight: Not determined Particle Size: Not applicable **Softening Point:** Not applicable Viscosity: Not determined Percent Volatile: Not determined Sat. Vap. Concentrat.: Not determined Molecular Formula: Not determined

# 10

# STABILITY AND REACTIVITY

Stability: This product is stable.

Conditions to avoid: Avoid excessive heat, sources of ingition and excessive water.

Materials to avoid (incompatability): Avoid contact with strong oxidizing agents and strong reducing agents (strong acids

or bases.) Avoid mixture with water.

**Hazardous Decomposition products:** Carbon monoxide, carbon dioxide, and various hydrocarbons.

**Hazardous Polymerization:** Will not occur.



# **GDL Garage Door Lube**

MSDS Number: GDL Aerosol Revision Date: 02/24/06

Page 4 of 5

# 11

# **TOXICOLOGICAL INFORMATION**

Toxicological information on this product as a mixture has not been determined. See section 15 for reportable ingredients.

# 12

# **ECOLOGICAL INFORMATION**

Ecological information on this product as a mixture has not been determined.

# 13

# **DISPOSAL CONSIDERATIONS**

Used or unused product should be disposed of in accordance with local, state, abd federal regulations. Some special regulations may exists for the disposal of empty aerosol containers.

Empty containers may contain residual pressure and contents. They should be handled with the same precautions as the product.

#### 14

### TRANSPORT INFORMATION

# Dept. of Transportation (DOT):

This product, as it leaves Blaster's facilities, meets the definitions set forth in CFR 49 part 173.150c as a "consumer commodity." Allowing for certain exceptions (173.156) for domestic surface (ground) shipments.

Proper shipping name: Consumer Commodity

Hazard class: ORM-D

# International (IMDT-IATA):

Proper shipping name: Aerosols, Limited Quantities

Hazard class: 2 Flammable Gas

UN Number: 1950

# 15

# **REGULATORY INFORMATION**

COMPONENT / (CAS/PERC) / CODES

\*Carbon dioxide (propellant) (124389 <2%) MASS, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS

REGULATORT RET DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level



# **GDL Garage Door Lube**

MSDS Number: GDL Aerosol Revision Date: 02/24/06

Page 5 of 5

16

# **OTHER INFORMATION**

### Manufacturer's Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither The Blaster Chemical Companies nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists.

**HMIS Ratings:** 

Health: 1 Fire: 2 Reacitivity: 0

**END OF MSDS DOCUMENT**