



## Material Safety Data Sheet

---

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identification

**Product ID:** 140.0017480  
**Product Name:** SEMI SLD WR REDWOOD VOC  
**Product Use:** Paint product.  
**Print date:** 24/Mar/2014  
**Revision Date:** 24/Mar/2014

#### Company Identification

The Valspar Corporation - Architectural Coatings Division  
1191 Wheeling Road  
Wheeling, IL 60090

**Manufacturer's Phone:** 1-847-520-8580

**24-Hour Medical Emergency Phone:** 1-888-345-5732

### 2. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Eye Contact:

- Moderate eye irritation
- Risk of serious damage to eyes.

#### Skin Contact:

- Causes skin irritation.
- Harmful if absorbed through skin.

#### Ingestion:

- Harmful if swallowed.

**Inhalation:**

- May cause irritation of respiratory tract.
- Harmful by inhalation.

**Target Organ and Other Health Effects:**

- Kidney injury may occur.
- Blood disorders
- Causes headache, drowsiness or other effects to the central nervous system.
- Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).
- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Chronic exposure may cause permanent damage of health.
- Prolonged exposure over TLV may produce pneumoconiosis.

**Carcinogens:**

- Cancer hazard. Contains material which can cause cancer.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
ETHYLENE GLYCOL MONOPROPYL ETHER 2807-30-9	1 - 5	Ethylene glycol monopropyl ether
PROPRIETARY INERT	1 - 5	PROPRIETARY INERT
COBALT NAPHTHENATE 61789-51-3	.1 - 1	Naphthenic acids, cobalt salts
SILICA 14808-60-7	.1 - 1	QUARTZ (SiO <sub>2</sub> )

If this section is blank there are no hazardous components per OSHA guidelines.

**4. FIRST AID MEASURES****Eye Contact:**

Remove any contact lenses and open eyes wide apart. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Never give anything by mouth to an unconscious person. Only induce vomiting at the instruction of medical personnel. Get medical attention.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

**5. FIRE FIGHTING MEASURES**

Flash point (Fahrenheit):	201
Flash point (Celsius):	94
Lower explosive limit (%):	1
Upper explosive limit (%):	16
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Avoid contact with eyes.

**7. HANDLING AND STORAGE****Precautions to be taken in handling and storage:**

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

**8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS****Personal Protective Equipment****Eye and face protection:**

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

**Skin protection:**

Appropriate chemical resistant gloves should be worn.

**Other Personal Protection Data:**

Ensure that eyewash stations and safety showers are close to the workstation location. To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

## Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture.

## Exposure Guidelines

### OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
PROPRIETARY INERT	1 - 5	20 mppcf or 80 mg/m <sup>3</sup> / %SiO <sub>2</sub>		
SILICA 14808-60-7	.1 - 1	(30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA, total dust (250)/(%SiO <sub>2</sub> + 5) mppcf TWA, respirable fraction (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA, respirable fraction		

### ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
COBALT NAPHTHENATE 61789-51-3	.1 - 1	0.02 mg/m <sup>3</sup> Co			
SILICA 14808-60-7	.1 - 1	0.025 mg/m <sup>3</sup> TWA respirable fraction			

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	24 mmHg @ 77°F (25°C)
Vapor density (air = 1.0):	3.6
Boiling point:	212°F (100°C)
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	8.73
Specific Gravity:	1.05
Evaporation rate (butyl acetate = 1.0):	0.2
Flash point (Fahrenheit):	201
Flash point (Celsius):	94
Lower explosive limit (%):	1
Upper explosive limit (%):	16
Autoignition temperature:	not determined

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Incompatibility:	Avoid water-reactive materials, heat or contact with peroxides or other catalysts.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.

## 10. STABILITY AND REACTIVITY

Sensitivity to static discharge:

Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
ETHYLENE GLYCOL MONOPROPYL ETHER 2807-30-9	1 - 5	= 3089 mg/kg Oral LD50 Rat = 960 µL/kg Dermal LD50 Rabbit
COBALT NAPHTHENATE 61789-51-3	.1 - 1	= 3900 mg/kg Oral LD50 Rat
SILICA 14808-60-7	.1 - 1	= 500 mg/kg Oral LD50 Rat

### Mutagens/Teratogens/Carcinogens:

Cancer hazard. Contains material which can cause cancer.

Contains crystalline silica. The IARC has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1). Refer to IARC monograph 68 in conjunction with the use of these materials. Risk of cancer depends on the duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles in spray mists. The NTP has also determined that crystalline silica is a known human carcinogen in the form of fine, breathable particles. Risk of cancer depends on duration and level of exposure in coatings products, risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
SILICA 14808-60-7	.1 - 1		Listed. initial date 10/1/88 - carcinogen

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
COBALT NAPHTHENATE 61789-51-3	.1 - 1			Monograph 52 [1991]
SILICA 14808-60-7	.1 - 1	Monograph 68 [1997]		

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens
SILICA 14808-60-7	.1 - 1	Known Human Carcinogen	

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
COBALT NAPHTHENATE 61789-51-3	.1 - 1	Present		Group A3 Confirmed animal carcinogen with unknown relevance to humans.
SILICA 14808-60-7	.1 - 1	Present		A2 Suspected Human Carcinogen

## 12. ECOLOGICAL DATA

No information on ecology is available.

### 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

### 14. TRANSPORTATION INFORMATION

#### U.S. Department of Transportation

UN ID Number (msds):

NRPAIN

Proper Shipping Name:

PAINT, NOT REGULATED

#### U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

#### Reportable Quantity Description:

#### International Air Transport Association (IATA):

Proper shipping name:

NOT REGULATED

#### International Maritime Organization (IMO):

Proper shipping name:

NOT REGULATED

Marine Pollutant

No

### 15. REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
ETHYLENE GLYCOL MONOPROPYL ETHER 2807-30-9	1 - 5		YES	
COBALT NAPHTHENATE 61789-51-3	.1 - 1		YES	

#### SARA 311/312 Hazard Class:

Acute: yes  
Chronic: yes  
Flammability: no  
Reactivity: no  
Sudden Pressure: no

#### U.S. STATE REGULATIONS:

#### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

**Pennsylvania Right To Know:**

ETHYLENE GLYCOL MONOPROPYL ETHER 2807-30-9  
PROPRIETARY INERT Trade Secret

**Additional Non-Hazardous Materials**

PROPRIETARY RESIN Trade Secret  
WATER 7732-18-5  
PROPRIETARY OIL Trade Secret

**California Proposition 65:**

WARNING! This product contains a chemical known in the State of California to cause cancer.

**Rule 66 status of product** Not photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories**

**US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION**

**HMIS Codes**

**Health:** 2\*  
**Flammability:** 0  
**Reactivity:** 1  
**PPE:** X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pinsky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

Prepared By: Regulatory Affairs Department  
Print date: 24/Mar/2014  
Revision Date: 24/Mar/2014

