30000 01 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER HMIS CODES

Health Flammability 2 Reactivity 0 30000

PRODUCT NAME

FORMBY'S* ALMOND LUSTRE*

MANUFACTURER'S NAME EMERGENCY TELEPHONE NO. FORMBY'S (216) 566-2917

10 Mountainview Road

Upper Saddle River, NJ 07458

DATE OF PREPARATION

INFORMATION TELEPHONE NO. 31-MAR-07 (800) 523-9299

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS
% by WT CAS No. INGREDIENT UNITS VAPOR PRESSURE 3 74-98-6 Propane ACGIH TLV 2500 ppm OSHA PEL 1000 ppm 760 mm 106-97-8 Butane ACGIH TLV 800 ppm OSHA PEL 800 ppm 760 mm 75-28-5 2-Methylpropane 3 ACGIH TLV Not Available OSHA PEL Not Available 760 mm 14 64741-66-8 Light Isoparaffinic HC Solvent ACGIH TLV Not Available OSHA PEL Not Available 36 mm ______

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist. EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.
SKIN: Prolonged or repeated exposure may cause irritation.
INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Continued on page 2

30000 page 2 ______

Section 4 -- FIRST AID MEASURES

Flush eyes with large amounts of water for 15 minutes.

Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If affected, remove from exposure. Restore breathing. Keep warm and quiet. INHALATION:

INGESTION: Do not induce vomiting.

Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

LEL UEL 1.3 10.2 FLASH POINT Propellant < 0 F EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Available

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate

readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take

internally. Keep out of the reach of children.

30000 page 3 ______

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

7.30 lb/gal 874 q/l PRODUCT WEIGHT 0.88 <0 - 284 F <-18 - 140 C SPECIFIC GRAVITY BOILING POINT MELTING POINT VOLATILE VOLUME EVAPORATION RATE VAPOR DENSITY SOLUBILITY IN WATER Hq

Not Available 95 % Faster than ether Heavier than air N.A. 7.0

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) Volatile Weight 24.98% Less Water and Federally Exempt Solvents

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable CONDITIONS TO AVOID None known. INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

30000 page 4

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA CAS No.	Ingredient N	ame					
74-98-6	Propane						
		LC50 LD50	RAT RAT	4HR		Available Available	
106-97-8	Butane						
		LC50	RAT	4HR	Not	Available	
		LD50	RAT		Not	Available	
75-28-5	2-Methylpropane						
		LC50	RAT	4HR	Not	Available	
		LD50	RAT		Not	Available	
64741-66-8	Light Isopar	affinic	HC Solve	ent			
	-	LC50	RAT	4HR	Not	Available	
		LD50	RAT		Not	Available	
===========	=========	======	======	======	====		

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Coation 14 EDANGDORE INFORMATION

Section 14 -- TRANSPORT INFORMATION

US Ground (DOT)

May be classed as Consumer Commodity, ORM-D UN1950, AEROSOLS, 2.2, LIMITED QUANTITY, (ERG#126)

Canada (TDG)

May be classed as Consumer Commodity, ORM-D UN1950, AEROSOLS, CLASS 2.2, (ERG#126)

IMO

May be shipped as Limited Quantity UN1950, AEROSOLS, CLASS 2, LIMITED QUANTITY, EmS F-D, S-U

Continued on page 5

3000	0			pag	re 5
	Section 15 REGULATORY INFORMATION				
SARA 313	(40 CFR 372.65C) SUPPLIER NOTIFICATION				
CAS No	. CHEMICAL/COMPOUND	%	by WT	% E	lement
	redients in this product are subject to SARA Notification.	313	(40 CFR	372	.65C)
All ch	IFICATION emicals in this product are listed, or are exCA Inventory.	xempt	from li	isti	ng,

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.