

# Material Safety Data Sheet

## For Coatings, Resins and Related Materials

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

24 Hour Emergency: 1-800-123-4567 CHEMTREC: 1-800-424-9300

National Response in Canada CANUTEC: 613-996-6666

Outside U.S. and Canada Chemtrec: 202-483-7616

### Section 1 - Chemical Product / Company Information

Product Name:	WATERBORNE CLEAR WOOD FINISH SATIN	Revision Date:	03/02/2012
Identification Number:	109	Print Date:	March 2, 2012
Product Use/Class:	WATERBORNE INTERIOR WOOD FINISH/UPC CODE = 037125109011	NSN:	NOT APPLICABLE
Manufacturer:	Deft, Inc. (CAGE CODE 33461) 17451 Von Karman Ave Irvine, Ca. 92614	Information Phone:	(949) 474-0400
		Emergency Phone:	(800) 424-9300

### Section 2 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: Harmful by inhalation, in contact with skin, and if swallowed. Contact with eyes or skin causes irritation.

**Effects Of Overexposure - Eye Contact:** Exposure to liquid, aerosol, or vapors may cause irritation, tearing, redness, and swelling accompanied by a stinging sensation. Direct eye contact may cause irritation. May cause temporary clouding of the cornea. May cause slight corneal damage.

**Effects Of Overexposure - Skin Contact:** Direct skin contact may cause irritation. Symptoms may include swelling, redness, and rash. Prolonged or repeated skin contact may cause dermatitis, drying, and defatting due to the solvent properties. Contact with skin may cause blistering. Skin contact with large amounts of a component may cause drowsiness.

**Effects Of Overexposure - Inhalation:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes) & acute nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness, or coma. Inhalation may cause headaches, difficult breathing, and loss of consciousness. Inhalation of a component may cause narcotic or anesthetic effects.

**Effects Of Overexposure - Ingestion:** Ingestion may cause gastrointestinal irritation, abdominal pain, nausea, vomiting, and diarrhea. May result in possible corrosive action in the mouth, stomach tissue, and digestive tract. Vomiting may cause aspiration of the solvent, resulting in chemical pneumonitis.

**Effects Of Overexposure - Chronic Hazards:** Prolonged contact will cause drying and cracking of the skin, due to defatting action. Skin sensitization, asthma, or other allergic responses may develop. 1-METHYL-2-PYRROLIDONE, CAS 872-50-4, (N-METHYL PYRROLIDONE) IS ON REACH SVHC CANDIDATE LIST.

**Primary Route(s) Of Entry:** Skin Contact, Inhalation, Eye Contact

### Section 3 - Composition / Information On Ingredients

<u>Component</u>	<u>CAS Number</u>	<u>Weight % Less Than</u>
DIPROPYLENE GLYCOL, n-BUTYL ETHER	29911-28-2	4.11
DIPROPYLENE GLYCOL MONOMETHYL ETHER	34590-94-8	4.06
1-METHYL-2-PYRROLIDONE	872-50-4	1.85

ALL INGREDIENTS ARE ON THE TSCA INVENTORY LIST, UNLESS OTHERWISE NOTED IN SECTION 8.

### Section 4 - First Aid Measures

**First Aid - Eye Contact:** If material gets into eyes, flush with water immediately for 15 minutes. Hold eyelids open to rinse out the entire eye. Consult a physician.

**First Aid - Skin Contact:** Remove contaminated clothing and shoes. In case of contact, immediately flush skin with plenty of water and wash affected areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse or discard.

**First Aid - Inhalation:** Move to fresh air in case of accidental inhalation of vapors. Asthmatic type

symptoms may develop and maybe immediate or delayed by several hours. In the case of inhalation of aerosol/mist, consult a physician, if necessary.

**First Aid - Ingestion:** Do not induce vomiting. Do not give anything to an unconscious person. Obtain medical help.

### Section 5 - Fire Fighting Measures

Flash Point (°F): >212 TCC LOWER EXPLOSIVE LIMIT UPPER EXPLOSIVE LIMIT (%): ND  
(%): 1.1

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Spray, Dry Sand, Dry Powder

Unusual Fire And Explosion Hazards: Keep containers tightly closed. Fire or intense heat may cause violent rupture of packages. Application to hot surfaces requires special precautions. Toxic gases may form when product burns.

Special Firefighting Procedures: In the event of fire, wear self-contained breathing apparatus. Firefighters should wear full protective clothing. Water mist may be used to cool closed containers. Cool fire-exposed containers using water spray.

### Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Use personal protective equipment as necessary. Dike to prevent entering any sewer or waterway. Absorb with inert material and collect for disposal.

### Section 7 - Handling and Storage

Handling: Prevent prolonged breathing of vapors or spray mist. Avoid contact with eyes and skin. Do not take internally. Do not handle until the manufacturers safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety practice. Use only in ventilated areas. Open doors and windows. Do not drill, solder, pressurize, grind, cut, weld, or braze empty container. Empty containers may contain vapors of a component(s).

Storage: Avoid storing near high temperatures, fire, open flames, and spark sources. Keep containers upright to prevent leakage and tightly closed in a dry, cool, and well-ventilated place. Protect from freezing in shipping and storage.

### Section 8 - Exposure Controls / Personal Protection

Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL
DIPROPYLENE GLYCOL, n-BUTYL ETHER	N.E.	N.E.	N.E.	N.E.
DIPROPYLENE GLYCOL MONOMETHYL ETHER	100 ppm	150 ppm	100 ppm	150 ppm
1-METHYL-2-PYRROLIDONE	N.E.	N.E.	N.E.	N.E.

### Notes

DOWANOL DPNB GLYCOL ETHER CAS # 29911-28-2 has been shown to cause effects to the respiratory tract and liver in animal studies. DIPROPYLENE GLYCOL MONOMETHYL ETHER CAS# 34590-94-8 has been shown to cause minor effects in the liver and kidneys of animals.

N-METHYLPYRROLIDONE, CAS # 872-50-4, estimated TLV TWA 100 ppm. (Per GAF Corporation). Exposure to high doses has been shown to cause testicular effects in rats. Was not carcinogenic to rats exposed through inhalation and food source over a lifetime. Mice that were exposed to high doses developed liver adenomas. Male mice also developed carcinomas. Middle does caused liver hypertrophy in male mice.

Engineering Controls: Local ventilation of emission sources may be necessary to maintain ambient concentrations below permissible OSHA exposure limits. Remove all ignition sources (heat, sparks, flame, and hot surfaces).

Respiratory Protection: A respirator that is recommended or approved for use in an organic vapor environment (air purifying, fresh air supplied, or NIOSH certified respirator for organic vapors, mists, and fumes) is necessary if OSHA/ACGIH permissible exposure limits are exceeded. Observe OSHA regulations for respirator use. Ventilation should be provided to keep exposure levels below OSHA/ACGIH permissible exposure levels.

Skin Protection: Solvent-resistant gloves.

Eye Protection: Wear safety eyewear (safety glasses, safety glasses with side-shields, chemical goggles, or face shields) to prevent eye contact.

Other protective equipment: Long sleeve and long leg clothing is recommended. Remove and wash contaminated clothing before reuse or discard. Safety shower and eyewash station should be located in immediate work area. Wear an apron and boots that are chemical-resistant.

Hygienic Practices: Wash hands before breaks, eating, smoking, using washroom, and at the end of the workday.

### Section 9 - Physical and Chemical Properties

Boiling Range (°F): 212 - 446 Vapor Density: Heavier than air

Odor:	Slight ammonia odor	Odor Threshold:	N.D.
Appearance:	Translucent liquid	Evaporation Rate:	ND
Solubility in H <sub>2</sub> O:	Soluble		
Freeze Point:	N.D.	Specific Gravity:	1.033
Vapor Pressure, mm Hg:	16.	PH:	> 7.5
Physical State:	Liquid	Viscosity:	57-61 KREBS UNITS (ca. 250-300 cps)

(See section 16 for abbreviation legend)

**Section 10 - Stability and Reactivity**

Conditions To Avoid: Do not breathe vapors or spray mist. Avoid processes that might generate static electrical discharge. Do not freeze.

Incompatibility: Material is incompatible with oxidizing agents, strong acids, and bases.

Hazardous Decomposition: Thermal decomposition can lead to the generation and release of gases and vapors including carbon monoxide, carbon dioxide, oxides of nitrogen, and hydrocarbons. Ketones, organic acids, and aldehydes may form.

Hazardous Polymerization: Will not occur.

Stability: Stable under recommended storage conditions.

**Section 11 - Toxicological Information**

Product LD50: N.E.

Product LC50: N.E.

**Section 12 - Ecological Information**

Ecological Information: No Information.

**Section 13 - Disposal Information**

Disposal Information: Dispose of waste in accordance with federal, state, and local environmental regulations.

**Section 14 - Transportation Information**

DOT Proper Shipping Name:	Paint	Packing Group:	NA
DOT Technical Name:	N.A.	Hazard Subclass:	N.A.
DOT Hazard Class:	NOT REGULATED	Resp. Guide Page:	N.A.
DOT UN/NA Number:	N.A.	IATA:	NOT REGULATED

**Section 15 - Regulatory Information**

The following components are not subject to reporting in Section 3:

<b><u>Component</u></b>	<b><u>CAS Number</u></b>	<b><u>Weight % Less Than</u></b>
WATER	7732-18-5	58.6488
ACRYLIC COPOLYMER	PROPRIETARY	27.5861
AMORPHOUS SILICA	7631-86-9	1.4263
WATER	7732-18-5	0.9448
POLYURETHANE	MIXTURE	0.4801
WETTING AGENT	TRADE SECRET	0.3557
POLYMER SOLUTION	NOT HAZARDOUS	0.2362
EMULSION OF POLYETHER-SILOXANE	PROPRIETARY	0.1507
POLYSILOXANE	PROPRIETARY	0.1
AMMONIA	7664-41-7	0.1
OCTAMETHYLCYCLOTETRA-SILOXANE	556-67-2	0.01

DEFT PROPRIETARY – THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION. DO NOT COPY, DISCLOSE TO OTHERS, OR PUBLISH WITHOUT WRITTEN PERMISSION FROM DEFT, INC.

**CERCLA – SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories: IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD

**SARA Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<b><u>Component</u></b>	<b><u>CAS Number</u></b>	<b><u>Percent By Weight</u></b>
1-METHYL-2-PYRROLIDONE	872-50-4	1.8511

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**Component**

DIPROPYLENE GLYCOL MONOMETHYL ETHER  
1-METHYL-2-PYRROLIDONE

**CAS Number**

34590-94-8  
872-50-4

**U.S. State Regulations: As follows –****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

**Component**

WATER  
ACRYLIC COPOLYMER

**CAS Number**

7732-18-5  
PROPRIETARY

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%.

**Component**

WATER  
ACRYLIC COPOLYMER

**CAS Number**

7732-18-5  
PROPRIETARY

**California Proposition 65:**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:  
None

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

**Component**

1-METHYL-2-PYRROLIDONE

**CAS Number**

872-50-4

**Percent By Weight**

1.8511

**International Regulations: As follows –**

**CANADIAN WHMIS:** This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** N.A.

**Section 16 - Other Information****HMIS Ratings:**

Health: 1

Flammability: 1

Reactivity: 0

Personal Protection: G

**NFPA Fire Rating: 1**

**NFPA Health Rating: 2**

**NFPA Specific Hazard Rating: NA**

**NFPA Stability Rating: 1**

**VOLATILE ORGANIC COMPOUNDS, GR/LTR: 270**

**VOLATILE ORGANIC COMPOUNDS, LB/GAL: 2.25**

**VOLATILE ORGANIC COMPOUNDS MIXED, GR/LTR: <= 275**

**VOLATILE ORGANIC COMPOUNDS MIXED, LB/GAL: <= 2.29**

**VOLATILE ORGANIC COMPOUNDS OF MATERIAL (SCAQMD RULE 443.1), GR/LTR: 104**

**VOLATILE ORGANIC COMPOUNDS OF MATERIAL (SCAQMD RULE 443.1), LB/GAL: 0.87**

**VOLATILE HAPs PER WEIGHT SOLIDS, LB./LB. 0**

**REASON FOR REVISION:** From: ROBERT\_HAMPTON@homedepot.com

[mailto:ROBERT\_HAMPTON@homedepot.com]

Sent: Thursday, March 01, 2012 12:39 PM

To: Katina Dinh

Subject: RE: MSDS WB CWF Product

It is my job to look at all the new products being on boarded to THD and classify them as hazardous or non-hazardous. We need all new products to state all of the ingredients, the % of those ingredients adding up to at least 100% (hazardous and non-hazardous) and the transportation information. If the product is regulated under DOT, which these products seem to be, I need the UN#, packaging group #, and hazard class #. The THD understands that this is above and beyond the normal requirements but all of this information is necessary for the safety of the THD workers and customers. So basically I need the

ingredient info adding up to at least 100% and the transportation info (UN#, Packaging group #, and Hazard class#) provided in either an email or a new MSDS.

Thanks!

Robert Hampton  
Home Depot SSC  
2455 Paces Ferry Rd. NW, C19  
Atlanta, GA. 30339  
Phone (770) 433-8211 X82693  
Robert\_Hampton@Homedepot.com

**REGULATORY CODE:** 109

**LAYOUT CODE:** A2004FD

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.