

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS Label element

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear eye protection/ face protection.
Wear protective gloves.
Response:

ASHLAND®		Page: 2
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

IF ON SKIN: Wash with plenty of soap and water.
 IF IN EYES: Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 If skin irritation or rash occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Not a hazardous substance or mixture.	28.96
DI-TERT-BUTYL POLYSULFIDE	68937-96-2	Flam. Liq. 4; H227 Skin Sens. 1B; H317	5.30
WHITE MINERAL OIL	8042-47-5	Not a hazardous substance or mixture.	3.08
Phosphoric acid esters, amine salt	91745-46-9	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 2; H401 Aquatic Chronic 2; H411	2.11

ASHLAND		Page: 3
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
May cause an allergic skin reaction.
Causes serious eye irritation.
- Notes to physician : No hazards which require special first aid measures.

ASHLAND®		Page: 4
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Sulphur oxides
Hydrogen chloride gas
Nitrogen oxides (NO_x)
Oxides of phosphorus
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

ASHLAND®		Page: 5
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRANS
WHITE MINERAL OIL	8042-47-5	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRANS
		TWA	5 mg/m3 Mist.	TN OEL

ASHLAND®		Page: 6
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

		TWA	5 mg/m3 Inhalable fraction.	ACGIH
--	--	-----	--------------------------------	-------

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : mild

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 626 °F / 330 °C
(1,013.333333 hPa)
Calculated Phase Transition Liquid/Gas

Flash point : > 390 °F / > 199 °C
Method: Cleveland open cup

Evaporation rate : < 1
Ethyl Ether

ASHLAND		Page: 8
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

Strong acids
Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide
Hydrocarbons
Hydrogen chloride gas
Nitrogen oxides (NOx)
Oxides of phosphorus
Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DI-TERT-BUTYL POLYSULFIDE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402

WHITE MINERAL OIL:

Acute oral toxicity : LD 50 (Rat): 50,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Phosphoric acid esters, amine salt:

Acute oral toxicity : LD 50 (Rat): 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

DI-TERT-BUTYL POLYSULFIDE:

ASHLAND®		Page: 9
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

Result: Slightly to moderately irritating to skin

WHITE MINERAL OIL:

Result: Not irritating to skin

Phosphoric acid esters, amine salt:

Result: Mildly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

DI-TERT-BUTYL POLYSULFIDE:

Result: Slightly irritating to eyes

WHITE MINERAL OIL:

Result: Not irritating to eyes

Phosphoric acid esters, amine salt:

Result: Severely irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

DI-TERT-BUTYL POLYSULFIDE:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 406

Phosphoric acid esters, amine salt:

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

DI-TERT-BUTYL POLYSULFIDE:

Genotoxicity in vitro : Test Type: in vitro assay
Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test
Test species: Mouse
Cell type: Bone marrow
Method: OECD Test Guideline 474
Result: negative

ASHLAND		Page: 10
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

DI-TERT-BUTYL POLYSULFIDE:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (*Daphnia magna*)): 0.24 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (*Pseudokirchneriella subcapitata* (microalgae)): 2.45 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (microalgae)): 0.1 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Method: OECD Test Guideline 201

ASHLAND®		Page: 11
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

Phosphoric acid esters, amine salt:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

DI-TERT-BUTYL POLYSULFIDE:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 13 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

Bioaccumulative potential

DI-TERT-BUTYL POLYSULFIDE:

Partition coefficient: n-octanol/water : log Pow: 5.6 (20 °C)
 pH: 7

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.

SAFETY DATA SHEET

Revision Date: 06/01/2015

Print Date: 6/24/2016

SDS Number: R0388288

Synpower™ 75W-140 LIMITED SLIP SYNTHETIC
GEAR OIL

Version: 1.2

VV982

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

MARINE
POLLUTANT:(
DI-TERT-
BUTYL
POLYSULFID
E)**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

ASHLAND®		Page: 13
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s) SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

NONHAZARDOUS COMPONENT(S)	Not Assigned	30.00 - 50.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	20.00 - 30.00 %
HYDROGENATED POLYDECENE	68037-01-4	20.00 - 30.00 %
DI-TERT-BUTYL POLYSULFIDE	68937-96-2	5.00 - 10.00 %
WHITE MINERAL OIL	8042-47-5	1.00 - 5.00 %
LUBRICANT ADDITIVE	Not Assigned	1.00 - 5.00 %

New Jersey Right To Know

NONHAZARDOUS COMPONENT(S)	Not Assigned	30.00 - 50.00 %
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	20.00 - 30.00 %
HYDROGENATED POLYDECENE	68037-01-4	20.00 - 30.00 %
DI-TERT-BUTYL POLYSULFIDE	68937-96-2	5.00 - 10.00 %
WHITE MINERAL OIL	8042-47-5	1.00 - 5.00 %

California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

ASHLAND		Page: 14
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- AUSTR : On the inventory, or in compliance with the inventory
- DSL : All components of this product are on the Canadian DSL.
- ENCS : Not in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/01/2015

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p> <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

ASHLAND®		Page: 15
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

H227	Combustible liquid.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H313	May be harmful in contact with skin.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.

Further information

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity

ASHLAND®		Page: 16
SAFETY DATA SHEET		Revision Date: 06/01/2015
		Print Date: 6/24/2016
		SDS Number: R0388288
Synpower™ 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL		Version: 1.2
VV982		

TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System