

Issuing Date 22-Oct-2009

Revision Date 03-May-2013

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Mothers PowerPlastic 4Lights

Product Code(s) 08808, 38808

Recommended Use Car care

Supplier Address

MOTHERS POLISHES WAXES CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

CAUTION!

Emergency Overview

May be harmful if swallowed

Appearance White

Physical State Liquid.

Odor Perfume

Potential Health Effects

Principle Routes of Exposure Inhalation. Skin contact. Eye contact.

Acute Toxicity

Eyes

May cause slight irritation.

Skin

Repeated exposure may cause skin dryness or cracking.

Inhalation

Avoid breathing vapors or mists. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing.

Ingestion

May be harmful if swallowed. Potential for aspiration if swallowed. May cause drowsiness and dizziness.

Chronic Effects

No known effect based on information supplied.

Aggravated Medical Conditions

Respiratory disorders. Pre-existing eye disorders. Skin disorders.

Environmental Hazard

See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Deodorized kerosene	8008-20-6	10-30
Calcined kaolin clay	66402-68-4	10-30
Isopropyl alcohol	67-63-0	< 10
Pseudocumene	95-63-6	< 1

4. FIRST AID MEASURES

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water. Consult a physician if necessary.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician.
Notes to Physician	Treat symptomatically.
Protection of First-aiders	Use personal protective equipment.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Not flammable.			
Flash Point	> 221.3 °F / > 105 °C			
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Explosion Data				
Sensitivity to Mechanical Impact	None.			
Sensitivity to Static Discharge	None			
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
NFPA	Health Hazard 1	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1	Flammability 0	Physical Hazard 0	Personal Protection X

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Avoid contact with the skin and the eyes. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.
Environmental Precautions	Prevent further leakage or spillage if safe to do so.
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other noncombustible absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling	Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists.
Storage	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Deodorized kerosene 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S*	-	TWA: 100 mg/m ³
Calcined kaolin clay 66402-68-4	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr TWA: 0.2 mg/m ³ Mn	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³ (vacated)	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
Mineral Spirits 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³ (vacated)	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Pseudocumene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m ³	TWA: 25 ppm TWA: 125 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm
Diethanolamine 111-42-2	TWA: 1 mg/m ³ inhalable fraction and vapor S*	(vacated) TWA: 3 ppm (vacated) TWA: 15 mg/m ³	TWA: 3 ppm TWA: 15 mg/m ³
Cupric nitrate 3251-23-8	TWA: 1 mg/m ³ Cu dust and mist	-	IDLH: 100 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ Cu dust and mist

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin and Body Protection

No special protective equipment required.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White.	Odor	Perfume.
Odor Threshold	No information available.	Physical State	Liquid.
pH	Approx. 9.0		
Flash Point	> 221.3 °F / > 105 °C	Autoignition Temperature	No information available.
Decomposition Temperature	No information available.	Boiling Point/Boiling Range	93.3 °C
Melting Point/Range	No information available.		
		Flammability Limits in Air	No information available.
Specific Gravity	1.008	Solubility	No information available.
Evaporation Rate	No information available.	Vapor Pressure	No data available.
Vapor Density	No data available.	Viscosity	600-900 cps

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	None known based on information supplied.
Conditions to Avoid	Do not freeze. Heat, flames and sparks.
Hazardous Decomposition Products	None under normal use. Thermal decomposition can lead to release of irritating gases and vapors. Carbon oxides.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information	No acute toxicity information is available for this product.
Inhalation	No known hazard by inhalation. Avoid breathing vapors or mists.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	Prolonged contact may cause redness and irritation.
Ingestion	No known effect.

Component Information

Chronic Toxicity

Carcinogenicity	Occupational health effects due to inhalation of mineral dusts incorporating crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc) graphite or coal unlikely to occur from exposure to this product.
------------------------	---

Chemical Name	ACGIH	IARC	NTP	OSHA
Deodorized kerosene	A3	Group 3		
Calcined kaolin clay		Group 2B		X
Isopropyl alcohol		Group 3		X

Sensitization	May cause sensitization by skin contact.
Target Organ Effects	Eyes. Respiratory system. Skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropyl alcohol	EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
Pseudocumene		LC50 96 h: 7.19-8.28 mg/L flow-through (Pimephales promelas)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Chemical Name		Log Pow		
Isopropyl alcohol		0.05		
Pseudocumene		3.63		

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to state and Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste pursuant to Federal regulations, and the applicable state requirements for the specific area of disposal. Consult the appropriate state, regional, or local regulations for additional requirements

Contaminated Packaging

Dispose of in accordance with local regulations.

Chemical Name	California Hazardous Waste
Calcined kaolin clay	Toxic soluble Toxic
Isopropyl alcohol	Toxic Ignitable
Pseudocumene	Toxic

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

15. REGULATORY INFORMATION

International Inventories
Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations**International Regulations****Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION**Prepared By**

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date

22-Oct-2009

Revision Date

03-May-2013

Revision Note

Update to Format, Product Code change

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet