

# Safety Data Sheet



## 1. Identification

|                             |                                                                                |                         |                                                                                |
|-----------------------------|--------------------------------------------------------------------------------|-------------------------|--------------------------------------------------------------------------------|
| <b>Product Name:</b>        | STRUST QT 2PK SATIN DOORPAINT<br>BLACK                                         | <b>Revision Date:</b>   | 11/11/2015                                                                     |
| <b>Product Identifier:</b>  | 238310                                                                         | <b>Supersedes Date:</b> | 5/15/2015                                                                      |
| <b>Product Use/Class:</b>   | Door Paint/Alkyd                                                               |                         |                                                                                |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department                                                          |                         |                                                                                |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700                                                  |                         |                                                                                |

## 2. Hazard Identification

### Classification

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

11% of the mixture consists of ingredient(s) of unknown acute toxicity.

### GHS HAZARD STATEMENTS

|                                        |      |                                      |
|----------------------------------------|------|--------------------------------------|
| Flammable Liquid, category 3           | H226 | Flammable liquid and vapor.          |
| Skin Irritation, category 2            | H315 | Causes skin irritation.              |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction. |
| Eye Irritation, category 2             | H319 | Causes serious eye irritation.       |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.                  |
| Germ Cell Mutagenicity, category 1B    | H340 | May cause genetic defects.           |
| Carcinogenicity, category 1B           | H350 | May cause cancer.                    |

### GHS LABEL PRECAUTIONARY STATEMENTS

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P201           | Obtain special instructions before use.                                                                                          |
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO SMOKING.                                   |
| P261           | Avoid breathing dust, fumes, gases, mists, vapors, or spray.                                                                     |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.                                                       |
| P281           | Use personal protective equipment as required.                                                                                   |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.                                                                                  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.                                                                           |
| P312           | Call a POISON CENTER or doctor/physician if you feel unwell.                                                                     |

P333+P313  
P337+P313  
P362

If skin irritation or rash occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing.

**GHS SDS PRECAUTIONARY STATEMENTS**

P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P363 Wash contaminated clothing before reuse.

**3. Composition/Information On Ingredients****HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>                                   | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u>    |
|--------------------------------------------------------|----------------|-------------------|--------------------|--------------------------|
| n-Butyl Acetate                                        | 123-86-4       | 10-25             | GHS02-GHS07        | H226-336                 |
| Solvent Naphtha, Light Aromatic                        | 64742-95-6     | 10-25             | GHS07-GHS08        | H304-332-340-350         |
| 1,2,4-Trimethylbenzene                                 | 95-63-6        | 2.5-10            | GHS02-GHS07-GHS08  | H226-304-315-319-332-335 |
| Acrylic Polymer                                        | Proprietary    | 2.5-10            | Not Available      | Not Available            |
| 1,3,5-Trimethylbenzene                                 | 108-67-8       | 2.5-10            | GHS02-GHS07        | H226-335                 |
| Xylene (mixed isomers)                                 | 1330-20-7      | 1.0-2.5           | GHS02-GHS07        | H226-315-319-332         |
| Diethylbenzene, Mixed Isomers                          | 25340-17-4     | 1.0-2.5           | Not Available      | Not Available            |
| Carbon Black                                           | 1333-86-4      | 1.0-2.5           | Not Available      | Not Available            |
| Stoddard Solvent                                       | 8052-41-3      | 0.1-1.0           | GHS08              | H304-372                 |
| Solvent Naphtha, Light Aromatic                        | 64742-95-6     | 0.1-1.0           | GHS07-GHS08        | H304-332                 |
| Ethylbenzene                                           | 100-41-4       | 0.1-1.0           | GHS02-GHS07-GHS08  | H225-304-332-373         |
| Additive (Surfactant/Defoamer/Drier/Rheology Modifier) | Proprietary    | 0.1-1.0           | Not Available      | Not Available            |
| Methyl Ethyl Ketoxime                                  | 96-29-7        | 0.1-1.0           | GHS05-GHS06        | H302-312-317-318-331     |

**4. First-aid Measures**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

**5. Fire-fighting Measures**

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may explode when exposed to extreme heat due to buildup of steam. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Eliminate all ignition sources; use explosion-proof equipment. Place material in a container and dispose of according to local, provincial, state and federal regulations. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use. Avoid excess heat. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials.

## 8. Exposure Controls/Personal Protection

| Chemical Name                                              | CAS-No.     | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|------------------------------------------------------------|-------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| n-Butyl Acetate                                            | 123-86-4    | 20.0                  | 150 ppm           | 200 ppm            | 150 ppm      | N.E.                 |
| Solvent Naphtha, Light Aromatic                            | 64742-95-6  | 15.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| 1,2,4-Trimethylbenzene                                     | 95-63-6     | 10.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Acrylic Polymer                                            | Proprietary | 10.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| 1,3,5-Trimethylbenzene                                     | 108-67-8    | 5.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Xylene (mixed isomers)                                     | 1330-20-7   | 5.0                   | 100 ppm           | 150 ppm            | 100 ppm      | N.E.                 |
| Diethylbenzene, Mixed Isomers                              | 25340-17-4  | 5.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Carbon Black                                               | 1333-86-4   | 5.0                   | 3 mg/m3           | N.E.               | 3.5 mg/m3    | N.E.                 |
| Stoddard Solvent                                           | 8052-41-3   | 1.0                   | 100 ppm           | N.E.               | 500 ppm      | N.E.                 |
| Solvent Naphtha, Light Aromatic                            | 64742-95-6  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Ethylbenzene                                               | 100-41-4    | 1.0                   | 20 ppm            | N.E.               | 100 ppm      | N.E.                 |
| Additive (Surfactant/Defoamer/<br>Drier/Rheology Modifier) | Proprietary | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Methyl Ethyl Ketoxime                                      | 96-29-7     | 1.0                   | 10 ppm            | N.E.               | N.E.         | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications. Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

## 9. Physical and Chemical Properties

|                                 |                     |                                                |           |
|---------------------------------|---------------------|------------------------------------------------|-----------|
| <b>Appearance:</b>              | Liquid              | <b>Physical State:</b>                         | Liquid    |
| <b>Odor:</b>                    | Solvent Like        | <b>Odor Threshold:</b>                         | N.E.      |
| <b>Relative Density:</b>        | 1.085               | <b>pH:</b>                                     | N.A.      |
| <b>Freeze Point, °C:</b>        | N.D.                | <b>Viscosity:</b>                              | N.D.      |
| <b>Solubility in Water:</b>     | Slight              | <b>Partition Coefficient, n-octanol/water:</b> | N.D.      |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                 | 1.0 - 8.0 |
| <b>Boiling Range, °C:</b>       | 112 - 168           | <b>Flash Point, °C:</b>                        | 27        |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-ignition Temp., °C:</b>                | N.D.      |
| <b>Evaporation Rate:</b>        | Slower than Ether   | <b>Vapor Pressure:</b>                         | N.D.      |
| <b>Vapor Density:</b>           | Heavier than Air    |                                                |           |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid temperatures above 120°F (49°C). Avoid contact with strong acid and strong bases. Avoid all possible sources of ignition.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes Serious Eye Irritation

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Prolonged or repeated skin contact may cause irritation. Causes skin irritation. Allergic reactions are possible.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. May cause headaches and dizziness. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. IARC lists Ethylbenzene as a possible human carcinogen (group 2B).

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>            | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u> |
|----------------|---------------------------------|------------------|---------------------|-------------------|
| 123-86-4       | n-Butyl Acetate                 | 10768 mg/kg Rat  | >17600 mg/kg Rabbit | > 21 mg/L Rat     |
| 64742-95-6     | Solvent Naphtha, Light Aromatic | 8400 mg/kg Rat   | >2000 mg/kg Rabbit  | N.I.              |
| 95-63-6        | 1,2,4-Trimethylbenzene          | 3280 mg/kg Rat   | >3160 mg/kg Rabbit  | 18 mg/L Rat       |
| 108-67-8       | 1,3,5-Trimethylbenzene          | N.I.             | N.I.                | 24 mg/L Rat       |
| 1330-20-7      | Xylene (mixed isomers)          | 3500 mg/kg Rat   | >4350 mg/kg Rabbit  | 29.08 mg/L Rat    |
| 1333-86-4      | Carbon Black                    | >15400 mg/kg Rat | N.I.                | N.I.              |

64742-95-6 Solvent Naphtha, Light Aromatic  
 100-41-4 Ethylbenzene  
 96-29-7 Methyl Ethyl Ketoxime

8400 mg/kg Rat  
 3500 mg/kg Rat  
 930 mg/kg Rat

>2000 mg/kg Rabbit  
 15400 mg/kg Rabbit  
 1100 mg/kg Rabbit

N.I.  
 17.2 mg/L Rat  
 >4.8 mg/L Rat

N.I. - No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components. Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

|                       | <u>Domestic (USDOT)</u>              | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>TDG (Canada)</u>                  |
|-----------------------|--------------------------------------|-----------------------------|-------------------|--------------------------------------|
| UN Number:            | N.A.                                 | 1263                        | 1263              | N.A.                                 |
| Proper Shipping Name: | Paint Products in Limited Quantities | Paint                       | Paint             | Paint Products in Limited Quantities |
| Hazard Class:         | N.A.                                 | 3                           | 3                 | N.A.                                 |
| Packing Group:        | N.A.                                 | III                         | III               | N.A.                                 |
| Limited Quantity:     | Yes                                  | Yes                         | Yes               | Yes                                  |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>                                   | <u>CAS-No.</u> |
|--------------------------------------------------------|----------------|
| 1,2,4-Trimethylbenzene                                 | 95-63-6        |
| Acrylic Polymer                                        | Proprietary    |
| Xylene (mixed isomers)                                 | 1330-20-7      |
| Ethylbenzene                                           | 100-41-4       |
| Additive (Surfactant/Defoamer/Drier/Rheology Modifier) | Proprietary    |

#### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

**16. Other Information****HMIS RATINGS**

Health: 1\*      Flammability: 3      Physical Hazard: 0      Personal Protection: X

**NFPA RATINGS**

Health: 1      Flammability: 3      Instability: 0

**VOLATILE ORGANIC COMPOUNDS, g/L:** 486

**SDS REVISION DATE:** 11/11/2015

**REASON FOR REVISION:** Product Composition Changed  
Substance and/or Product Properties Changed in Section(s):  
01 - Identification  
02 - Hazard Identification  
05 - Fire-fighting Measures  
09 - Physical & Chemical Properties  
15 - Regulatory Information  
16 - Other Information  
Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.