

# Safety Data Sheet

according to OSHA Hazard Communication  
29 CFR Part 1910.1200



## Section 1. Identification

**Identification Number:** 8-1434  
**Product Name:** NWP SOLID COL WD STN-REDWOOD  
**Product Use/Class:** Solid Latex Stain

### SUPPLIER:

Yenkin-Majestic Paint Corporation  
1920 Leonard Avenue  
Columbus, OH 43219

CHEMTREC 1-800-424-9300  
24 Hr. Emergency Hotline

**Safety Data Sheet Coordinator:** J. Michael Jacobs (614) 253-8511

### MANUFACTURER:

Yenkin-Majestic Paint Corporation  
1920 Leonard Avenue  
Columbus, OH 43219

CHEMTREC 1-800-424-9300  
24 Hr. Emergency Hotline

## Section 2. Hazard(s) Identification

**EMERGENCY OVERVIEW:** Harmful if swallowed.

### GHS Classification

No GHS classifications were found for this product

### Symbol(s) of Product

No GHS symbols exist for this product

### Signal Word

No signal word has been assigned to this product

## Section 3. Composition/Information on Ingredients

| <u>Chemical Name</u>                                 | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|------------------------------------------------------|----------------|--------------|--------------------|-----------------------|
| No hazardous materials are contained in this product |                |              |                    |                       |

## Section 4. First-Aid Measures



**FIRST AID - INHALATION:** No Information

**FIRST AID - SKIN CONTACT:** Wash with soap and water. Get medical attention if irritation develops or persists.

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention if irritation persists.

**FIRST AID - INGESTION:** If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**MOST IMPORTANT SYMPTOMS:** Eye irritation signs/symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Skin irritation signs/symptoms may include a burning sensation, redness, swelling, and/or blisters.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION IF NECESSARY:** If symptoms persist call a poison control center or a

doctor/physician.

## Section 5. Fire-Fighting Measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No Information

**SPECIAL FIREFIGHTING PROCEDURES:** Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Move containers from fire area if it can be done without risk.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

## Section 6. Accidental Release Measures

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** Stop leak if you can do so without risk.

**ENVIRONMENTAL PRECAUTIONS:** Prevent entry into waterways, sewers, basements, and other confined spaces.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Contain and absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

## Section 7. Handling and Storage



**HANDLING:** Wash thoroughly after handling.

**STORAGE:** Keep container closed when not in use. Keep from freezing.

## Section 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

| Chemical Name | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|---------------|---------------|----------------|--------------|------------------|
|---------------|---------------|----------------|--------------|------------------|

No hazardous items exist in this product

**Legend:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### Protective Measures



**ENGINEERING CONTROLS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Good ventilation should be sufficient to control excessive odor.



**RESPIRATORY PROTECTION:** No Information



**SKIN PROTECTION:** The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Rubber, nitrile or neoprene to prevent skin contact.



**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.



**OTHER PROTECTIVE EQUIPMENT:** Wear chemical resistant shoes. Rubber or plastic apron should be worn.



**HYGIENIC PRACTICES:** Wash hands before eating. Remove contaminated clothing and wash before reuse. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing.

## Section 9. Physical and Chemical Properties

|                                 |                           |                                                     |          |
|---------------------------------|---------------------------|-----------------------------------------------------|----------|
| <b>Appearance:</b>              | Red Liquid                | <b>Physical State:</b>                              | Liquid   |
| <b>Odor:</b>                    | Typical Latex             | <b>Odor Threshold:</b>                              | N.D.     |
| <b>Specific Gravity:</b>        | 1.152                     | <b>pH:</b>                                          | 9.0-9.5  |
| <b>Freeze Point, °C:</b>        | 0                         | <b>Viscosity:</b>                                   | 70-75 KU |
| <b>Solubility in Water:</b>     | Soluble                   | <b>Partition Coefficient, n-octanol/<br/>water:</b> | N.D.     |
| <b>Decomposition Temp., °C:</b> | N.D.                      | <b>Explosive Limits, vol%:</b>                      | N.A.     |
| <b>Boiling Range, °C:</b>       | 100 - 196                 | <b>Flash Point, °C:</b>                             | >93.3    |
| <b>Evaporation Rate:</b>        | Slower than Diethyl Ether | <b>Vapor Pressure:</b>                              | N.D.     |
| <b>Vapor Density:</b>           | Lighter than air          |                                                     |          |

(See "Other information" Section for abbreviation legend)

## Section 10. Stability and Reactivity

**REACTIVITY:** No Information

**STABILITY:** This product is stable under normal storage conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** None under normal processing conditions.

**CONDITIONS TO AVOID:** Do not freeze. High temperatures or high humidity.

**INCOMPATIBILITY:** Strong acids or strong bases.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: Carbon Monoxide, Carbon Dioxide and various other hydrocarbons.

## Section 11. Toxicological Information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Proper respiratory equipment MUST be worn when sanding or abrading surfaces painted with this product. Sanding or abrading the dried paint film increases the risk of exposure. When incorporated in the liquid paint, pigments or extenders pose minimal risk of exposure. No hazard in normal use.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Causes skin irritation. Allergic reactions are possible.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** No Information

**EFFECT OF OVEREXPOSURE - INGESTION:** This material may be irritating to the mouth, throat, and stomach.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### STOT - SINGLE EXPOSURE

No Additional Information

### STOT - REPEATED EXPOSURE

No Additional Information

**Carcinogenicity:** The information below indicates whether each agency has listed any ingredient as a carcinogen if present at levels greater than or equal to 0.1 %.

| <u>CAS-No.</u> | <u>Name</u> | <u>NTP</u> | <u>OSHA</u> | <u>IARC</u> |
|----------------|-------------|------------|-------------|-------------|
|----------------|-------------|------------|-------------|-------------|

No hazardous materials are contained  
in this product

National Toxicological Program (NTP), Occupational Safety & Health Association (OSHA), International Agency for Research on Cancer (IARC) Group 1: Carcinogenic to Humans, Group 2A: Probably Carcinogenic to Humans, Group 2B: Possibly Carcinogenic to Humans, Group 3: Not Classifiable as to its Carcinogenicity to Humans

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Name according to EEC | Oral LD50 (mg/kg) | Dermal LD50 (mg/kg) | Vapor LC50 (mg/L) |
|---------|-----------------------|-------------------|---------------------|-------------------|
|---------|-----------------------|-------------------|---------------------|-------------------|

No hazardous materials are contained in this product

## Section 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

**MOBILITY IN SOIL:** No Information

**OTHER ADVERSE EFFECTS:** No Information

## Section 13. Disposal Considerations



Product

**DISPOSAL METHOD:** Dispose of in accordance with all local, state, and federal regulations. Approved incinerator or approved hazardous waste facility. Dried material may be disposed of in landfill. If liquid is present, add adsorbent (such as cat litter) and stir until there is no free liquid remaining and dispose of properly.

## Section 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

**ENVIRONMENTAL HAZARDS:** No Information

**TRANSPORT IN BULK:** See DOT Information below.

|                                  |               |                          |      |
|----------------------------------|---------------|--------------------------|------|
| <b>DOT Proper Shipping Name:</b> | NOT REGULATED | <b>Packing Group:</b>    | N.A. |
| <b>DOT UN/NA Number:</b>         | N.A.          | <b>Hazard SubClass:</b>  | N.A. |
| <b>DOT Hazard Class:</b>         | N.A.          | <b>Resp. Guide Page:</b> | N.A. |
| <b>DOT Technical Name:</b>       | N.A.          |                          |      |
| <b>Exception:</b>                | N.A.          |                          |      |

## Section 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| Chemical Name                    | CAS-No.    |
|----------------------------------|------------|
| 3-iodo-2-propynylbutyl carbamate | 55406-53-6 |
| ethylene glycol monobutyl ether  | 111-76-2   |
| ethylene glycol (HAP)            | 107-21-1   |

**TOXIC SUBSTANCES CONTROL ACT:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

**U.S. State Regulations:****PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%. For hazardous components see Section 3.

| <u>Chemical Name</u>               | <u>CAS-No.</u> |
|------------------------------------|----------------|
| H2O                                | 7732-18-5      |
| ACRYLIC POLYMER                    | Proprietary    |
| CALCIUM CARBONATE                  | 1317-65-3      |
| SODIUM POTASSIUM ALUMINUM SILICATE | 37244-96-5     |

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

| <u>Chemical Name</u>        | <u>CAS-No.</u> |
|-----------------------------|----------------|
| MAGNESIUM ALUMINUM SILICATE | 12174-11-7     |
| CRYSTALLINE SILICA          | 14808-60-7     |
| CARBON BLACK                | 1333-86-4      |

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

**International Regulations: As follows -****CANADIAN REGULATORY INFORMATION:**

This SDS has been prepared in compliance with Hazardous Product Regulations (HPR).

Canadian DSL: No Information

**Section 16. Other Information, Including Date of Preparation of the Last Revision**

Revision Date: 3/8/2017 Supercedes Date: 1/24/2017

Datasheet produced by: Regulatory Department

**HMIS Ratings:**

Health: 1 Flammability: 0 Reactivity: 0 Personal Protection: B

Volatile Organic Compounds, lb/gal: 0.81

Volatile Organic Compounds, gr/ltr: 97

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information, STOT - Specific Target Organ Toxicity, MIR - Maximum Incremental Reactivity

The information on this safety data sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product, or where instructions and recommendations are not followed. The user assumes all risks incident to the use of the product and must communicate to employees and customers all warnings that relate to the potential exposure to this product. It is the responsibility of the user to comply with all Federal, State, and Local laws, regulations, and ordinances, and to assure that all workplace and disposal practices are in compliance with such. ALL WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. IN NO EVENT SHALL THE SUPPLIER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.