

SAFETY DATA SHEET

Issue Date 24-Apr-2015

Revision Date 10-May-2015

Version 2

1. IDENTIFICATION

Product identifier Product Name

Henry 208R Rubberized Wet Patch Roof Cement

Other means of identification Product Code Synonyms

HE208R None

Recommended use of the chemical and restrictions on useRecommended UseSealant.Uses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: 800-486-1278 Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Emergency Telephone

CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning



Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

In case of fire: Use Water spray, fog or regular foam for extinction

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

29.97% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum Asphalt	8052-42-4	30 - 60	*
Calcium carbonate	1317-65-3	10 - 30	*
Stoddard solvent	8052-41-3	10 - 30	*
1,2,4 Trimethylbenzene	95-63-6	0.1 - 1	*
QUARTZ	14808-60-7	<0.1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.			
Skin contact	Wash skin with soap and water.			
Inhalation	Remove to fresh air.			
Ingestion Clean mouth with water and drink afterwards plenty of water.				
Most important symptoms and effe	ects, both acute and delayed			
Symptoms	Drowsiness.			
Indication of any immediate medica	al attention and special treatment needed			
Note to physicians	Treat symptomatically.			
	5. FIRE-FIGHTING MEASURES			
	appropriate to local circumstances and the surrounding environment.			
Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.				
Specific hazards arising from the c No information available.	hemical			
<u>Explosion data</u> Sensitivity to Mechanical Impac Sensitivity to Static Discharge	ct None. None.			
Protective equipment and precauti As in any fire, wear self-contained bre protective gear.	ons for firefighters eathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions, protective e	guipment and emergency procedures			
Personal precautions	Ensure adequate ventilation, especially in confined areas.			
Environmental precautions				
Environmental precautions	See Section 12 for additional ecological information.			
Methods and material for containm	ent and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.			
Methods for cleaning up	Pick up and transfer to properly labeled containers.			
	7. HANDLING AND STORAGE			

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat,
	sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min
Calcium carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
QUARTZ 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	 (vacated) TWA: 0.1 mg/m³ respirable dust : (30)/(%SiO2 + 2) mg/m³ TWA total dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction 	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Drovided in accordance with current local redulations.	• •	respiratory protection should be worn. Positive-pressure supplied air respirat required for high airborne contaminant concentrations. Respiratory protection		
	ection must be	required for high airborne contaminant concentrations. Respiratory protection provided in accordance with current local regulations.		
			neral Hygiene Considerations	Gen
General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.		ral Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.	neral Hygiene Considerations	Gen

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Petroleum distillates No information available

Physical state Appearance Color	liquid paste black	Odor Odor threshold
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air	<u>Values</u> No information available No information available >= $150 \ ^{\circ}C$ 40 $\ ^{\circ}C$ No information available No information available	<u>Remarks • Method</u>
Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Relative density Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	9% 1% No information available No information available 0.9 - 1.3 No information available No information available No information available No information available >100 mm2/s No information available No information available No information available	@ 40 °C
Other Information Softening point Molecular weight VOC Content (%) Density Bulk density	No information available No information available No information available No information available No information available	

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability

Stable under recommended storage conditions. Possibility of Hazardous Reactions None under normal processing. Conditions to avoid Extremes of temperature and direct sunlight. Incompatible materials Strong oxidizing agents. Hazardous Decomposition Products None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

No data available

Inhalation

May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat)4 h
QUARTZ 14808-60-7	= 500 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms

Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No informatio	No information available. No information available. No information available.		
Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum Asphalt 8052-42-4	-	Group 2B	-	Х
QUARTZ 14808-60-7	A2	A2 Group 1 Known X		
Reproductive toxicity STOT - single exposure STOT - repeated exposur Aspiration hazard	No information re No information	No information available. No information available. No information available. No information available.		

Numerical measures of toxicity - Product Information

ATEmix (oral)	5,602.00
ATEmix (dermal)	5,602.00
ATEmix (inhalation-gas)	99,999.00
ATEmix (inhalation-dust/mist)	14.01
ATEmix (inhalation-vapor)	99,999.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

49.4 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

Not readily biodegradable.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Petroleum Asphalt 8052-42-4	>6
1,2,4 Trimethylbenzene 95-63-6	3.63

Other adverse effects

No information available

Ozone	Not applicable			
13. DISPOSAL CONSIDERATIONS				
Waste treatment methods				
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.			
Contaminated packaging	Do not reuse container.			

14. TRANSPORT INFORMATION

DOT	Not regulated (If shipped in NON BULK packaging by ground transport)
<u>TDG</u>	Not regulated
IATA UN/ID no. Proper shipping name Hazard Class Packing Group	UN1999 Tars, Liquid 3 III
IMDG UN/ID no. Proper shipping name Hazard Class Packing Group Description	UN1999 Tars, Liquid 3 III May be transported as non-hazardous in accordance with IMDG 2.3.2.5

15. REGULATORY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances **PICCS** - Philippines Inventory of Chemicals and Chemical Substances **AICS** - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

10-May-2015

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X
Issue Date	24-Apr-20			

Revision Date Revision Note No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet