



The Armor All/STP Products Company
 39 Old Ridgebury Road
 Danbury, CT 06810
 Tel. 1-203-205-2900

Material Safety Data Sheet

I Product:	ARMOR ALL® EXTREME TIRE SHINE-AEROSOL	
Description:	CLEAR, COLORLESS, SLIGHTLY VISCOUS LIQUID WITH SOLVENT ODOR	
Other Designations	Distributor	Emergency Telephone Nos.
	The Armor All/STP Products Company 39 Old Ridgebury Road Danbury, CT 06810	For Medical Emergencies call: 1-866-949-6465. For Transportation Emergencies call: 1-800-424-9300 (Chemtrec).

II Health Hazard Data	III Hazardous Ingredients		
Liquid can be irritating to eyes and skin. Vapors may cause irritation to the nose, throat, and respiratory tract. Repeated or prolonged exposure to high concentrations may cause central nervous system depression (e.g., dizziness, weakness, nausea, headaches and/or unconsciousness). Small amounts of liquid aspirated into the lungs can cause potentially fatal chemical pneumonitis. Solvents similar to this product have caused adverse kidney effects in male rats after prolonged and repeated inhalation exposure. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.	<u>Ingredients</u>	<u>Concentration</u>	<u>Worker Exposure Limit</u>
FIRST AID: INGESTION: DO NOT INDUCE VOMITING. Get prompt medical attention. EYE CONTACT: Remove contact lenses. Immediately flush eyes. thoroughly with plenty of water for 15 minutes. Get medical attention. SKIN CONTACT: Remove contaminated clothing. Wash area with soap and water. If irritation persists, get medical attention. INHALATION: Remove to fresh air. If breathing problems or irritation persist, get medical attention.	Petroleum Distillates CAS # 64742-47-8	60 - 75%	100 ppm TLV-TWA ^{a,b}
	Silicone Fluid CAS# N/A	15 - 25%	Not established
	Liquefied petroleum gas CAS#68476-85-7	7-12%	1000ppm-TLV-TWA ^a 1000ppm-PEL-TWA ^c
	^a TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average ^b Based on ACGIH TLV-TWA for stoddard solvent. ^c PEL-TWA = OSHA Permissible Exposure Limit-Time Weighted Average		
	None of the ingredients in the product are on the IARC, NTP or OSHA carcinogen list.		

IV Special Protection and Precautions	V Transportation and Regulatory Data
<u>Hygienic Practices:</u> Wash hands with soap and water after use. Do not wear product-contaminated clothing for prolonged periods. <u>Engineering Controls:</u> Use local and general ventilation to minimize exposure to vapor or mists. <u>Work Practices:</u> Wear safety glasses or goggles. Avoid eye and skin contact and inhalation of vapor or mist. Wear material resistant gloves if handling product for prolonged or repeated periods. Use a NIOSH-approved respirator if exposure may exceed occupational exposure limits. Contents under pressure. Keep away from heat, sparks, and open flame. Do not puncture or incinerate container. Exposure to temperatures above 130F may cause bursting. Store in a cool, dry area away from heat or open flame. KEEP OUT OF REACH OF CHILDREN	<u>DOT:</u> Consumer commodity ORM-D <u>IMDG:</u> UN 1950, Aerosols, Class 2.1, Ltd. Qty <u>IATA:</u> UN 1950, Aerosols, Class 2.1 <u>TSCA Status:</u> All ingredients in this product are listed on the TSCA inventory. <u>EPA - SARA Title III/CERCLA:</u> Packaged product is not reportable under Sections 311/312. Product contains no ingredients regulated under SARA 311/312; SARA 313, or SARA 304/CERCLA.

VI Spill Procedures/Waste Disposal	VII Reactivity Data
<u>Spill Procedures:</u> FLAMMABLE. Eliminate potential sources of ignition. Absorb and containerize. Do not wash down sanitary sewer. <u>Waste Disposal:</u> Dispose of in accordance with all applicable federal, state and local regulations.	Stable under normal use and storage conditions. Avoid strong oxidizing agents.

VIII Fire and Explosion Data	IX Physical Data
<u>Flashpoint:</u> ~170.0°F <u>Fire Extinguishing Agents:</u> Water, water fog, dry chemical, foam or carbon dioxide (CO ₂) fire extinguishers. Do not use a direct stream of water. <u>NFPA Aerosol Classification:</u> Level 3	Density 6.75lb/gal @ 70F Viscosity.....24, +10/ -6cP