Page 1 of 5 Thursday, August 30, 2012

MSDS - Material Safety Data Sheet Product Name: ENGINE BRIGHT ENGINE DEGREASER - ORIGINAL

MSDS No.: EB1CA

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY

Address: 600 RADIATOR ROAD

City, ST Zip: INDIAN TRAIL, NC 28079

Country:

Information Telephone Number: 704-684--181 1

Emergency Contact: RMPDC (877-740-5015) Emergency Telephone Number: 303-623-5716

Emergency Restrictions:

Contact: Robert Geer

Product Name: ENGINE BRIGHT ENGINE DEGREASER - ORIGINAL

MSDS No.: EB1CA

Issue Date: 08/30/2012 **Supersedes Date:** 10/22/2010

II. Hazards Identification:

EMERGENCY OVERVIEW

Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Contents Under Pressure.

Level 3 Aerosol

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Route(s) of Entry:

Absorption, Eye, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

See signs and symptoms below

Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis. Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis..

Ingestion: HARMFUL OR FATAL IF SWALLOWED.

Medical Conditions Generally Aggravated by Exposure:

None Known

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
Petroleum naphtha	64742-94-5	1.0 - 5.0	
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1.0	
Carbon dioxide	124-38-9	1.0 - 5.0	
Hydrocarbon Fluid	64742-47-8	30.0 - 60.0	
Naphthalene	91-20-3	1.0 - 5.0	
Petroleum distillate, Aliphatic	68476-34-6	30.0 - 60.0	
Polyoxyethylene Hexaoleate	57171-56-9	1.0 - 5.0	
Tripropylene Glycol Monomethyl Ether	25498-49-1	1.0 - 5.0	
Xylene (mixed isomers)	1330-20-7	0.1 - 1.0	

Page 2 of 5 Thursday, August 30, 2012

MSDS - Material Safety Data Sheet Product Name: ENGINE BRIGHT ENGINE DEGREASER - ORIGINAL

MSDS No.: EB1CA

IV. First Aid Measures:

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse

Inhalation: Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

Note to Physicians:

N/E

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

Unsuitable Extinguishing Media:

Do not use forced water stream as this could cause the fire to spread.

Products of Combustion:

High temperatures and ignition sources produce products of combustion: carbon monoxide, sulfur-like smoke.

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

VI. Accidental Release Measures:

Personal Precautions:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

Methods for Containment:

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

Methods for Cleanup:

Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

VII. Handling and Storage:

Handling Precautions:

Handling: Use with adequate ventilation and proper protective equipment.

Do not use near fire, sparks, or flame. Do not puncture or incinerate container. Avoid contact with eyes. Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits, use a NIOSH approved respirator to prevent over-exposure.

Storage Precautions:

Store in cool, well ventilated area below 120°F away from heat sources. Do not store with oxidizers.

VIII. Exposure Controls/Personal Protection:

MSDS - Material Safety Data Sheet Product Name: ENGINE BRIGHT ENGINE DEGREASER - ORIGINAL

MSDS No.: EB1CA

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Petroleum distillate, Aliphatic	N/E	100 ppm	N/E
Petroleum naphtha	N/E	N/E	100 ppm
Carbon dioxide	N/AV	5000 ppm	Not Available
Naphthalene	10 ppm	10 ppm	Not Available
Xylene (mixed isomers)	100 ppm	100 ppm	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Polyoxyethylene Hexaoleate	N/E	N/E	Not Available
Hydrocarbon Fluid	5 mg/m3	5 mg/m3	Not Available
Tripropylene Glycol Monomethyl Ether	N/E	N/E	Not Available

Engineering Controls:

See Section above for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

IX. Physical and Chemical Properties:

Boiling Point: 305°F Melting Point: N/A

Boiling Range: Not Available Freezing Point: Not Available

Solubility In Water: Emulifies Evaporation Rate (Butyl Acetate = 1): N/D

Flash Point: 165°F Flash Point Method: TCC

Odor Threshold: Not Available Appearance and Odor: Amber liquid with petroleum odor

Vapor Density (AIR = 1): 1.2Vapor Pressure (mm Hg.): N/DpH Range: Not AvailablePartition Coefficient: Not AvailableDecomposition Temp: Not AvailableAuto-Ignition Temp: Not Available

Lower Explosive Limit: N/E Upper Explosive Limit: N/E

Specific Gravity (H20 = 1): 0.86

Other Information: VOC Content: <10.0%

X. Stability and Reactivity:

Stability:

Stable

Conditions to Avoid:

See Incompatible Materials below.

Incompatible Materials:

Strong oxidizing agents.

Hazardous Decomposition Products:

High temperatures and ignition sources produce products of combustion: carbon monoxide, sulfur-like smoke.

Possibility of Hazardous Reactions:

Will not occur.

Page 4 of 5 Thursday, August 30, 2012

MSDS - Material Safety Data Sheet Product Name: ENGINE BRIGHT ENGINE DEGREASER - ORIGINAL

MSDS No.: EB1CA

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

DOT Subsidiary Hazard Class: Not Available

XIV. Transport Information:

Shipping Name: Not Available

DOT Hazard Class: Not Available

UN/NA#: Not Available Packing Group: Not Available

<u>Transportation Information:</u>
DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

UN number: UN1950 Shipping Name: Aerosols

Class: 2.1

IMDG

UN number: UN1950 Shipping Name: Aerosols

Class: 2.1 EmS: F-D, S-U

XV. Regulatory Information:

SARA 313 Reportable Chemicals: Aromatic Petroleum Distillate 64742-94-5 Xylene 1330-20-70 Naphthalene 91-20-3

1,2, 4-Trimethylbenzene 95-63-6

USA TSCA: All components of this material are listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

State RTK Chemicals: Xylene 1330-20-70 Naphthalene 91-20-3

MSDS - Material Safety Data Sheet Product Name: ENGINE BRIGHT ENGINE DEGREASER - ORIGINAL

MSDS No.: EB1CA

XVI. Other Information:							
Chemical State:	X Liquid	Gas	Solid	NFPA	Fire		
Chemical Type:	Pure	X Mixture	_	Health	2 Reastivity		
Hazard Category:				2	0		
X Acute	Chronic Pressure	X Fire Reactive			Special		
Additional Manufacture	er Warnings:						
Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY		2	Health				
FROM CHILDREN AND ANIMALS!			2	Flammability			
N/E: Not Established				0	Physical Hazard		
N/D: Not Determined				В	Pers. Protection		
N/A: Not Applicable							

Additional Product Information:

N/AV: Not Available

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.