

MATERIAL SAFETY DATA SHEET – SC 3100 Series 50 VOC

PRODUCT NAME: DECK & DOCK
PRODUCT CODE: SC-3101-SC-3104

HMIS CODES: H₁ F₀ R₀ P_B
D.O.T. CLASS: NOT REGULATED

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: DUCKBACK PRODUCTS, INC.
ADDRESS: P.O. BOX 980, 2644 HEGAN LANE, CHICO, CA 95927
EMERGENCY PHONE: CHEM TEL (24 HOUR) (800) 255-3924 **DATE PRINTED:** 05/18/2011
INFORMATION PHONE: (800) 825-5382 **PREPARED BY:** DUCKBACK PRODUCTS

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION

REPORTABLE COMPONENTS:	ACGIH TLV / TWA	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
PROPYLENE GLYCOL	NA	57-55-6	<1 @ 25°C	< 2

* CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372. THIS INFORMATION MUST BE INCLUDED IN ALL MSDS'S THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.

****WARNING:** THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A
FLASH POINT: NONE METHOD USED: N/A
BOILING RANGE: 212 DEG F SPECIFIC GRAVITY (H2O=1): 1.25
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: <50 GRAMS/LITER MATERIAL V.O.C.: <20 GRAMS/LITER
SOLUBILITY IN WATER: COMPLETE DENSITY: 10.43 LB / GAL
APPEARANCE: VARIES DEPENDING ON COLOR ODOR: SLIGHT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: USE WATER FOG, FOAM, DRY CHEMICAL, OR CO2.
SPECIAL FIRE FIGHTING PROCEDURES: MATERIAL IS NOT CONSIDERED A FIRE HAZARD. USE STANDARD FIRE FIGHTING TECHNIQUES TO EXTINGUISH FIRES INVOLVING THIS MATERIAL.
UNUSUAL FIRE AND EXPLOSION PROCEDURES: MATERIAL DOES NOT CONTRIBUTE TO ANY UNUSUAL HAZARDS WHEN INVOLVED IN A FIRE. AS IN ANY FIRE, PREVENT, HUMAN EXPOSURE TO FIRE, SMOKE, FUMES, OR PRODUCTS OF COMBUSTION.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID: KEEP FROM FREEZING. AVOID EXTREME HEAT, POOR VENTILATION, CORROSIVE ATMOSPHERES, AND EXCESSIVE AGING.
INCOMPATIBILITY: (MATERIALS TO AVOID): ALKALINE MATERIAL, STRONG ACIDS, AND OXIDIZING MATERIALS.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR



SECTION VI - ACUTE & CHRONIC HEALTH HAZARDS

INHALATION: OVEREXPOSURE TO VAPORS MAY CAUSE DIZZINESS, BREATHING DIFFICULTY, HEADACHES AND LOSS OF COORDINATION.

EYE CONTACT: MAY CAUSE BURNING. IN CASE OF CONTACT, FLUSH EYES WITH PLENTY OF WATER.

SKIN CONTACT: LIQUID MAY BE SLIGHTLY IRRITATING TO THE SKIN.

INGESTION: INGESTION OF PRODUCT CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

SIGNS & SYMPTOMS: EFFECTS OF OVEREXPOSURE MAY INCLUDE IRRITATION OF THE NOSE AND THROAT, IRRITATION OF THE DIGESTIVE TRACT AND SIGNS OF NERVOUS SYSTEM DEPRESSION INCLUDING HEADACHE, DROWSINESS, DIZZINESS, LOSS OF COORDINATION AND FATIGUE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: THERE IS NO DATA AVAILABLE WHICH ADDRESS MEDICAL CONDITIONS WHICH ARE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

CARCINOGENICITY: NTP CARCINOGEN: **NO** IARC MONOGRAPHS: **NO** OSHA REGULATED: **NO**

SECTION VII - FIRST AID MEASURES

INHALATION: MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION.

EYE: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN AND GET MEDICAL ATTENTION IF ANY IRRITATION PERSISTS.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE RE-USE.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: PROVIDE GOOD VENTILATION, DIKE SPILL AREA AND ADD SUITABLE ABSORBENT TO SPILLED LIQUID, PLACE ABSORBED MATERIAL INTO A SEALED METAL CONTAINER FOR PROPER DISPOSAL.

WASTE DISPOSAL METHOD: DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL. DISPOSE OF EMPTY CONTAINERS AND ABSORBED SPILL MATERIALS AND ANY UNUSED PRODUCT IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: WEAR PROTECTIVE CLOTHING WHEN USING. USE IN WELL VENTILATED AREA. STORE IN COOL, DRY, WELL-VENTILATED AREA. EXERCISE DUE CAUTION TO PREVENT DAMAGE TO THE CONTAINER. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE. PROTECT FROM FREEZING.

OTHER PRECAUTIONS: NONE

SECTION IX - CONTROL MEASURES

RESPIRATORY PROTECTION: WEAR A VAPOR / MIST RESPIRATOR (NIOSH / MSHA TC 23C OR EQUIVALENT) DURING SPRAY APPLICATIONS OR WHEN VENTILATION IS INADEQUATE TO PREVENT INHALATION OVEREXPOSURE.

VENTILATION: GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE ADEQUATE TO PREVENT OVEREXPOSURE.

PROTECTIVE GLOVES: USE IMPERMEABLE CHEMICAL HANDLING GLOVES FOR SKIN PROTECTION.

EYE PROTECTION: USE CHEMICAL SAFETY GLASSES, GOGGLES, OR FACE SHIELD FOR EYE PROTECTION.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: USE IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT.

WORK / HYGIENIC PRACTICES WHEN USING PRODUCT DO NOT EAT, DRINK, OR SMOKE. WASH HANDS THOROUGHLY AFTER USING.

SECTION X - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY DUCKBACK PRODUCTS, INC. TO BE ACCURATE, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

