

Material Safety Data Sheet

May be used to comply with OSHA'S Hazard Communication Standard, 29CFR1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Admin. (Non-Mandatory Form)

Section I

IDENTITY: (As used on label and list) **WALNUT SHELL**

Manufacturer's Name: Eco-Shell, Inc.
 Emergency Telephone Number: (530) 824-8794 or (530) 529-1585
 Address: 5230 Grange Road, Corning, CA 96021
 Telephone for Information: (530) 824-8794

Section II – Hazardous Ingredients/Identity Information

The chemicals listed under section II of the MSDS for this product is not reportable under SARA 313. If the product is reportable under this regulation, it will be noted in section II.

Section III

Boiling Point	N/A	Specific Gravity (H2O-1)	1.2
Vapor Pressure (MM Hg)	N/A	Melting Point	N/A
Vapor Density (Air – 1)	N/A	Evaporation	N/A

Solubility in water:	Not water soluble
Odor and appearance:	No odor – Light brown in color
Flash Point:	380°F
Flammable limits:	470°F
Media used in extinguishing:	Water
Special fire fighting procedure:	None

Fire and Explosion Hazards:

If improperly handled, stored and/or exposed to and ignition source, this material may burn. High concentrations of dust in air can explode if sufficient temperature and ignition source occurs.

Section IV – Health Hazard Data

No Acute Hazards Known

Section V – Reactivity Data

Stability:	Stable
Incompatibility (Materials to avoid)	None
Hazardous Polymerization:	None

Section VI – Health Hazards (Acute and Chronic)

None Known

Steps to be taken if material is released or spilled:

Sweep, Shovel up, or Vacuum

Waste Disposal Methods:

No special requirements

Precautions to be take in handling and storing:

None

Other Precautions:

None

Section VIII – Control Measures

Ventilation: Local Exhaust

Nuisance Dust Levels

Protective clothing, gloves, or equipment:

Not required

Eye Protection:

Not required – Safety goggles recommended

Ground English Walnut Shell

PROPERTIES:

Dual Screen Aggregates have the following characteristics

SPECIFIC GRAVITY	1.2 – 1.4
pH VALUE AT 25°C (IN WATER)	4-6
FREE MOISTURE (80°C FOR 15HRS)	3-9%
FLASH POINT (CLOSED CUP)	380°
HARDNESS -VICKERS NO	25-30
MOHS SCALE	3-4
DRY PACKING DENSITY (LBS PER CU. FT.)	22-74

GSA Specification:	AA-1722	Type 2
Military Specification:	MIL-G-5634	Type 3

CHEMICAL ANALYSIS

Nitrogen	0.10
Cellulose	40/60
Lignin	20/30
Toluene Solubility	0.5/1.0
Methoxyl	6.5
Chlorine	0.10
Ash	1.5
Cutin	1.0

Eco-Shell, Inc.
 5230 Grange Road
 Corning, CA 96021
 Phone: 1-(530)-824-8794
 FAX: 1-(530)-824-8798