

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY**SPECIALTY
FLUORESCENT SPRAYS****DESCRIPTION AND USES**

Fluorescent sprays provide bright, highly visible colors on a variety of surfaces. They are ideal for indoor and outdoor projects such as crafts, hobbies, stenciling, marking, and color coding. These paints also glow under ultraviolet (black) light. For best results, apply over a white base coat.

PRODUCTS**FINISHES**

1932830	Green
1942830	Yellow
1954830	Orange
1955830	Red-Orange
1959830	Pink

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. LEAD IS TOXIC. Contact the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)**PRIMING**

Use of a Rust-Oleum® primer provides superior adhesion and hiding and is especially recommended for bare wood and metal. Apply an undercoat of primer on darker surfaces for maximum brilliance.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY AND RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes and fully dry in 24 hours. Recoat at any time.

CLEAN UP

Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

SPECIALTY FLUORESCENT SPRAYS

PHYSICAL PROPERTIES

		FLUORESCENTS
Resin Type		Modified Acrylic Lacquer
Pigment Type		Varies with color
Fill Weight		11 oz.
MIR		1.4 Max
Solvents		Acetone, Toluene, Xylene, Hexane
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils
Practical Coverage at Recommended DFT (assumes 15% material loss)		10-12 sq. ft./can (0.9-1.09 m ² /can)
Dry Times at 77°F (25°C) and 50% Relative Humidity	Tack-free	15 minutes
	Handle	30 minutes
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Safety Information	Flash Point	Below 0°F (-18°C)
	Contains	Lead-free
	Warning!	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.