



## Material Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 3M™ Bondo Fiberglass Resin Kit, P.N. 420, 420M, 420C, 420E, 420ES, 420K, 420T, 422, 422M, 422C  
**MANUFACTURER:** 3M  
**DIVISION:** Automotive Aftermarket  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 03/21/13  
**Supersedes Date:** 11/14/12

**Document Group:** 24-2334-1

### ID Number(s):

60-4550-5647-7, 60-4550-5648-5, 60-4550-5657-6, 60-4550-6593-2, 60-4550-6595-7

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:**

24-2331-7, 24-2330-9

Revision Changes:  
Kit: ID Number(s) was modified.  
Copyright was modified.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a

particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

**3M USA MSDSs are available at [www.3M.com](http://www.3M.com)**



## Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M™ Bondo® Fiberglass Resin for Fiberglass Resin Kit, P.N. 420, 420C, 420ES, 420T, 422, 422C

**MANUFACTURER:** 3M

**DIVISION:** Automotive Aftermarket

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 04/16/13

**Supersedes Date:** 08/04/11

**Document Group:** 24-2330-9

#### Product Use:

Intended Use: Automotive

Specific Use: Fiberglass Repair Resin

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYESTER POLYMER	Trade Secret	40 - 70
SILICA	7631-86-9	0.5 - 1.5
STYRENE MONOMER	100-42-5	30 - 60

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Paste

**Odor, Color, Grade:** Pungent organic odor. Light straw color.

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. Contains a chemical or chemicals which can cause cancer.

## 3.2 POTENTIAL HEALTH EFFECTS

### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Prolonged or repeated exposure may cause:

Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and /or respiratory reaction, and changes in immune function.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u><b>Ingredient</b></u>	<u><b>C.A.S. No.</b></u>	<u><b>Class Description</b></u>	<u><b>Regulation</b></u>
STYRENE MONOMER	100-42-5	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical

attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	80 °F - 82 °F [Test Method: Closed Cup]
Flammable Limits(LEL)	1.1 %
Flammable Limits(UEL)	No Data Available
OSHA Flammability Classification:	Class IC Flammable Liquid

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Water may be used to blanket the fire. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

<b>Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.</b>
--

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

### 6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

#### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Seal the container.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## **SECTION 7: HANDLING AND STORAGE**

### **7.1 HANDLING**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Avoid breathing of vapors, mists or spray. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid contact with oxidizing agents. Avoid skin contact.

### **7.2 STORAGE**

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Do not store containers on their sides. Store away from oxidizing agents. Store away from strong bases.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1 ENGINEERING CONTROLS**

Use in an enclosed process area is recommended. Provide appropriate local exhaust for cutting, grinding, sanding or machining. Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

### **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

#### **8.2.1 Eye/Face Protection**

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles

.

#### **8.2.2 Skin Protection**

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Polyvinyl Alcohol (PVA)

.

#### **8.2.3 Respiratory Protection**

Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### **8.2.4 Prevention of Swallowing**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u><b>Ingredient</b></u>	<u><b>Authority</b></u>	<u><b>Type</b></u>	<u><b>Limit</b></u>	<u><b>Additional Information</b></u>
SILICA	CMRG	TWA, as respirable dust	3 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of particles/cu. ft.	
STYRENE MONOMER	ACGIH	TWA	20 ppm	
STYRENE MONOMER	ACGIH	STEL	40 ppm	
STYRENE MONOMER	OSHA	TWA	100 ppm	
STYRENE MONOMER	OSHA	CEIL	200 ppm	

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Specific Physical Form:</b>	Paste
<b>Odor, Color, Grade:</b>	Pungent organic odor. Light straw color.
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	80 °F - 82 °F [ <i>Test Method:</i> Closed Cup]
<b>Flammable Limits(LEL)</b>	1.1 %
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Boiling Point</b>	180 °F - 415 °F
<b>Density</b>	1.14 g/ml
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	3.45 mmHg
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Specific Gravity</b>	1.14 [ <i>Ref Std:</i> WATER=1]
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Solubility In Water</b>	<i>No Data Available</i>
<b>Solubility in Water</b>	Negligible
<b>Evaporation rate</b>	[ <i>Details:</i> Slower than ether.]
<b>Hazardous Air Pollutants</b>	33.8 % weight [ <i>Test Method:</i> Calculated]
<b>Volatile Organic Compounds</b>	386 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]
<b>Volatile Organic Compounds</b>	33.8 % weight [ <i>Test Method:</i> calculated per CARB title 2]
<b>Kow - Oct/Water partition coef</b>	<i>No Data Available</i>
<b>Percent volatile</b>	33.8 % weight
<b>Percent volatile</b>	42.61 % volume
<b>VOC Less H2O &amp; Exempt Solvents</b>	386 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]
<b>Viscosity</b>	<i>No Data Available</i>

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:**

**10.1 Conditions to avoid**

Heat  
Sparks and/or flames

**10.2 Materials to avoid**

Strong acids  
Strong bases  
Strong oxidizing agents

Additional Information: Storage at elevated temperatures will shorten shelf life.

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products**

**Substance**

Hydrocarbons  
Carbon monoxide  
Carbon dioxide

**Condition**

Not Specified  
Not Specified  
Not Specified

**Hazardous Decomposition:** Normal use of this product can generate styrene oxide (CAS No. 96-09-3). Styrene oxide is listed as a Group 2A carcinogen by IARC and is listed as a carcinogen in the California Proposition 65 regulations.

**SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

**SECTION 12: ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION**

Not determined.

**CHEMICAL FATE INFORMATION**

Not determined.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.



## SECTION 14: TRANSPORT INFORMATION

LB-K100-0410-5, LB-K100-0410-8, LB-K100-0543-7

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
STYRENE MONOMER	100-42-5	30 - 60

### STATE REGULATIONS

Contact 3M for more information.

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

#### NFPA Hazard Classification

Health: 2 Flammability: 3 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

#### Revision Changes:

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 3: Potential effects from inhalation information was modified.

Section 10: Hazardous decomposition or by-products table was modified.  
Section 8: Respiratory protection - recommended respirators information was modified.  
Section 8: Respiratory protection - recommended respirators was modified.  
Page Heading: Product name was modified.  
Section 9: Density information was modified.  
Section 9: Vapor density value was modified.  
Section 9: Vapor pressure value was modified.  
Section 9: Boiling point information was modified.  
Section 5: Flammable limits (UE) information was modified.  
Section 5: Flammable limits (LEL) information was modified.  
Section 5: Autoignition temperature information was modified.  
Section 9: Vapor density text was modified.  
Section 9: Vapor pressure text was modified.  
Section 5: Flash point information was modified.  
Section 9: Property description for optional properties was modified.  
Section 9: Specific gravity information was modified.  
Section 9: pH information was modified.  
Section 9: Melting point information was modified.  
Section 9: Solubility in water value was modified.  
Section 9: Solubility in water text was modified.  
Section 8: Respiratory protection - recommended respirators guide was modified.  
Section 9: Flash point information was modified.  
Section 9: Flammable limits (LEL) information was modified.  
Section 9: Flammable limits (UEL) information was modified.  
Section 9: Autoignition temperature information was modified.  
Section 2: Ingredient table was modified.  
Section 15: EPCRA 313 information was modified.  
Section 8: Exposure guidelines ingredient information was modified.  
Section 3: Carcinogenicity table was modified.  
Copyright was modified.  
Section 8: Respiratory protection - recommended respirators punctuation was deleted.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

**3M USA MSDSs are available at [www.3M.com](http://www.3M.com)**



## Material Safety Data Sheet

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M™ Bondo® MEKP Liquid Hardener for Fiberglass Resin Kit P.N. 420, 420C, 420E, 420K, 420T, 422, 422C

**MANUFACTURER:** 3M

**DIVISION:** Automotive Aftermarket

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000

**EMERGENCY PHONE:** 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 11/09/12

**Supersedes Date:** 08/09/12

**Document Group:** 24-2331-7

#### Product Use:

Intended Use: Automotive  
Specific Use: Curing Agent

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
DIMETHYL PHTHALATE	131-11-3	30 - 60
METHYL ETHYL KETONE PEROXIDE	1338-23-4	15 - 40
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	6846-50-0	10 - 30
METHYL ETHYL KETONE	78-93-3	1 - 5
HYDROGEN PEROXIDE	7722-84-1	0.5 - 1.5
WATER	7732-18-5	0.5 - 1.5

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** Slight odor. Clear.

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause chemical

eye burns. May cause severe skin irritation. May cause chemical gastrointestinal burns. May cause target organ effects.

## **3.2 POTENTIAL HEALTH EFFECTS**

### **Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

### **Skin Contact:**

Severe Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Prolonged or repeated exposure may cause:

Dermal Effects: Signs/symptoms may include changes in skin pigmentation and/or coloration.

### **Inhalation:**

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May be absorbed following ingestion and cause target organ effects.

### **Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## **SECTION 4: FIRST AID MEASURES**

### **4.1 FIRST AID PROCEDURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### **5.1 FLAMMABLE PROPERTIES**

**Autoignition temperature**

*No Data Available*

Flash Point	> 200 °F [ <i>Test Method:</i> Closed Cup] [ <i>Details:</i> No flash to boiling point.]
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Water may be used to blanket the fire. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Avoid contact with incompatible materials listed in the Reactivity Data Section. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

### 6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Dispose of collected material as soon as possible.

### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Seal the container.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid

breathing of vapors, mists or spray. Avoid skin contact. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid breathing of dust created by cutting, sanding, grinding or machining. Avoid contact with oxidizing agents.

## **7.2 STORAGE**

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container tightly closed. Store away from oxidizing agents. Store in a cool, dry place.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1 ENGINEERING CONTROLS**

Provide appropriate local exhaust for cutting, grinding, sanding or machining. Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

### **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

#### **8.2.1 Eye/Face Protection**

Avoid eye contact. Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles

.

#### **8.2.2 Skin Protection**

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Polymer laminate

.

#### **8.2.3 Respiratory Protection**

Avoid breathing of vapors, mists or spray. Avoid breathing of dust created by cutting, sanding, grinding or machining.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece supplied-air respirator

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

#### **8.2.4 Prevention of Swallowing**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### **8.3 EXPOSURE GUIDELINES**

<b><u>Ingredient</u></b>	<b><u>Authority</u></b>	<b><u>Type</u></b>	<b><u>Limit</u></b>	<b><u>Additional Information</u></b>
DIMETHYL PHTHALATE	ACGIH	TWA	5 mg/m3	
DIMETHYL PHTHALATE	OSHA	TWA	5 mg/m3	
HYDROGEN PEROXIDE	ACGIH	TWA	1 ppm	
HYDROGEN PEROXIDE	OSHA	TWA	1.4 mg/m3	
METHYL ETHYL KETONE	ACGIH	TWA	200 ppm	
METHYL ETHYL KETONE	ACGIH	STEL	300 ppm	
METHYL ETHYL KETONE	OSHA	TWA	590 mg/m3	

METHYL ETHYL KETONE PEROXIDE      ACGIH      CEIL      0.2 ppm

**SOURCE OF EXPOSURE LIMIT DATA:**

ACGIH: American Conference of Governmental Industrial Hygienists  
 CMRG: Chemical Manufacturer Recommended Guideline  
 OSHA: Occupational Safety and Health Administration  
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Odor, Color, Grade:</b>	Slight odor. Clear.
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	> 200 °F [ <i>Test Method:</i> Closed Cup] [ <i>Details:</i> No flash to boiling point.]
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Boiling Point</b>	244 °F
<b>Density</b>	1.128 g/ml
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Specific Gravity</b>	1.128 [ <i>Ref Std:</i> WATER=1]
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Solubility In Water</b>	<i>No Data Available</i>
<b>Solubility in Water</b>	Negligible
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Hazardous Air Pollutants</b>	43.0 % weight [ <i>Test Method:</i> Calculated]
<b>Volatile Organic Compounds</b>	903 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]
<b>Volatile Organic Compounds</b>	80.0 % weight [ <i>Test Method:</i> calculated per CARB title 2]
<b>Kow - Oct/Water partition coef</b>	<i>No Data Available</i>
<b>Percent volatile</b>	9.7 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	913 g/l [ <i>Test Method:</i> calculated SCAQMD rule 443.1]
<b>Viscosity</b>	<i>No Data Available</i>

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:**

**10.1 Conditions to avoid**

Light  
 Sparks and/or flames  
 Temperatures above the boiling point

**10.2 Materials to avoid**

Strong oxidizing agents  
 Alkali and alkaline earth metals

Strong acids

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

### CHEMICAL FATE INFORMATION

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable), D003 (Reactive), D035 (Methyl ethyl ketone)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

LB-K100-0410-6, LB-K100-0414-7

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):



<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
DIMETHYL PHTHALATE	131-11-3	30 - 60

## STATE REGULATIONS

Contact 3M for more information.

## CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

The components of this product are listed on the Canadian Domestic Substances List.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

**This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

**Health:** 3 **Flammability:** 1 **Reactivity:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** 3 **Flammability:** 1 **Reactivity:** 1 **Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

### Revision Changes:

Section 13: EPA hazardous waste number (RCRA) information was modified.

Section 6: Personal precautions information was modified.

Section 6: Environmental procedures information was modified.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

**3M USA MSDSs are available at [www.3M.com](http://www.3M.com)**